

Allen & Heath ZED-436 Specs

Total # Of Inputs	36
Mic/Line Inputs	32 x 3-Pin XLR Female Mic Inputs (Balanced) 32 x 1/4" TRS Line Inputs (Balanced/Unbalanced)
Stereo Line Inputs	4 x 1/4" TRS Line Inputs (Two Stereo Pairs, Balanced/Unbalanced)
In-Line Inputs>Returns	No
Aux Sends	6 x 1/4" TRS Mono (Balanced)
Aux Returns	4 x RCA Coaxial Line Inputs (Two Stereo Pairs, Unbalanced)
Inserts	32 x 1/4" TRS on Mono Channels (Unbalanced) 4 x 1/4" TRS on Group Buses (Unbalanced) 2 x 1/4" TRS on Stereo Main Bus (Unbalanced) 1 x 1/4" TRS on Mono Main Bus (Unbalanced)
Channel Direct Out	32 x 1/4" TRS (Balanced)
BUS (Group) Outputs	4 x 1/4" TRS Group Outputs (Balanced)

2 x 1/4" TRS Matrix Outputs
(Balanced)

Main Outputs 3 x 3-Pin XLR Male (One Stereo Pair
and One Mono, Balanced)

Monitor Outputs 1 x 1/4" TRS Stereo Headphone
Output (Unbalanced)
1 x 1/8" / 3.5 mm TRS Stereo
Headphone Output (Unbalanced)

2-Track I/O 2 x RCA Coaxial 2-Track Input (One
Stereo Pair, Unbalanced)
2 x RCA Coaxial 2-Track Output (One
Stereo Pair, Unbalanced)

ALT I/O 1 x USB Type-B (2-Channel
Send/Return)

Talkback Mic Input 1 x 3-Pin XLR Female (Balanced)

EQ Section High (All Channels): ± 15 dB Shelving
Filter at 12 kHz
High-Mid (Mono Channels): ± 15 dB
Peaking Filter at Selectable Frequency
(500 Hz to 15 kHz, Sweepable)
High-Mid (Stereo Channels): ± 15 dB
Peaking Filter at 2.5 kHz
Low-Mid (Mono Channels): ± 15 dB
Peaking Filter at Selectable Frequency
(35 Hz to 1 kHz, Sweepable)
Low-Mid (Stereo Channels): ± 15 dB
Peaking Filter at 250 Hz
Low (All Channels): ± 15 dB Shelving
Filter at 80 Hz

High-Pass Filter 12 dB/Octave at 100 Hz, Switchable

Solo/Mute	Mute and PFL Solo
Channel Level Control	100mm Fader
Trim/Gain Control	Rotary Control
Gain Range	Mic Inputs: -6 to +63 dB Line Inputs: -10 to +26 dB Stereo Inputs: $-\infty$ to +10 dB Faders: $-\infty$ to +10 dB Returns: $-\infty$ to +10 dB Aux Masters: $-\infty$ to +10 dB Matrix Levels: $-\infty$ to +6 dB
Phantom Power	+48 VDC, Selectable per Channel
Metering	Dual 12-Segment LEDs 4-Segment LED per Group Output 4-Segment LED per Main Output Signal LED per Channel Peak LED per Channel
USB Specification	USB 1.1 Compliant
Bit Depth	USB: 16-Bit
Sample Rates	USB: 32 kHz, 44.1 kHz, or 48 kHz
Nominal Input Level	Mic Input: -63 to +6 dBu Mono Line Input: -26 to +10 dBu Stereo Line Input: 0 dBu (+10 dB with Control Off) Insert Point: 0 dBu
Maximum Input Level	Mic Input: +17 dBu

Mono Line Input: +30 dBu
Insert Point: +21 dBu

Nominal Output Level

XLR Main Outputs: +4 dBu
Group Outputs: +4 dBu
Aux Outputs: -2 dBu
Matrix Outputs: -2 dBu
Inserts: -2 dBu
2-Track Output: 0 dBu
Direct Output: 0 dBu

Maximum Output Level

XLR Main Outputs: +27 dBu
Group Outputs: +27 dBu
Aux Outputs: +21 dBu
Matrix Outputs: +21 dBu
Inserts: +21 dBu
2-Track Output: +21 dBu
Direct Output: +21 dBu

Frequency Response

Mic In to Main Out (30 dB Gain): 20 Hz to 20 kHz (+0.5 dB, -1 dB)
Line In to Main Out (0 dB Gain): 10 Hz to 30 kHz (+0.5 dB, -1 dB)
Stereo In to Main Out: 10 Hz to 30 kHz (+0.5 dB, -1 dB)

THD + N

Mic In to Main Out (0 dB Gain, 1 kHz, +10 dBu Out): 0.004%
Mic In to Main Out (30 dB Gain, 1 kHz): 0.014%
Line In to Main Out (0 dB Gain, 1 kHz, 0 dBu): 0.005%
Stereo In to Main Out (0 dB Gain, 1 kHz, +10 dBu): 0.003%

Headroom

Analog Headroom from Nominal (0 VU): 21 dB
USB In and Out Headroom from Nominal (0 VU): 14 dB

Noise	Mic Pre EIN: -127 dBu (Maximum Gain, 150-Ohm Input, 22 Hz to 22 kHz) Mix Noise: -88 dB (-84 dBu) (L/R Out, 32 Channels Routed, Ref +4 dBu, 22 Hz to 22 kHz)
-------	--

Power Consumption	60 W Maximum
-------------------	--------------

Power Requirements	100 to 240 VAC, 47 to 63 Hz
--------------------	-----------------------------

Dimensions (W x H x D)	44.7 x 5.1 x 22.1" / 113.5 x 12.9 x 56.0 cm
------------------------	---

Weight	48.5 lb / 22 kg
--------	-----------------

Packaging Info

Package Weight	74 lb
----------------	-------

Box Dimensions (LxWxH)	50 x 28 x 10.5"
------------------------	-----------------
