

All Specifications

Display

Projection System	DLP
Resolution	XGA, 1024 x 768
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
Brightness (ANSI lumens)	3600
Contrast Ratio (FOFO)	15000:1
Display Color	30 Bits (1,07 billion colors)
Native Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Light Source	Lamp
Light Source Wattage	203W
Light Source life*	5000/10000/15000 hrs (Normal/Eco/SmartEco)

Optical

Throw Ratio	1.94-2.32 (60"@ 2.37m)
Zoom Ratio	1.2X
Lens	(5G all glass optical lens) F=2.46-2.66 f=21.8-25.6
Keystone Adjustment	1D, Vertical +/- 40 degrees
Projection Offset**	106%±5%
Clear Image Size (Diagonal)	60"~300"
Image Size	30"~300"
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120KHz

Audio

Speaker 2W x 1

Interface

PC (D-sub) 2

Monitor out (D-sub 15pin) 1

S-Video in (Mini DIN 4pin) 1

Composite Video in (RCA) 1

HDMI 2 (1.4a)

USB Type Mini B 1 (Download & Page up/down)

Audio in (3.5mm Mini Jack) 1

Audio out (3.5mm Mini Jack) 1

RS232 (DB-9pin) 1

IR Receiver 1 (Front)

Security Bar 1

Compatibility

HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Video Compatibility NTSC, PAL, SECAM

Environment

Power Supply AC 100 to 240 V, 50/60 Hz

Typical Power Consumption 252W(Normal)

Standby Power Consumption <0.5W

Acoustic Noise (Typ./Eco.) 32/29 dB, C sku: <36dB follow CECP

Operating Temperature 0~40°C

Dimension and Weight

Dimensions (W x H x D)(mm)	332.4 x 241.3 x 99
Net Weight (Kg/ lbs)	2.38 Kg (5.24lb)

Accessories (Standard)

Carton	Brown Carton, Hand Carry Type
Remote Control w/ Battery	1 (RCX013)
Power Cord (by region)	Yes
User Manual CD	Yes
Quick Start Guide	Yes
Warranty Card (by region)	Yes
VGA(D-sub 15pin) Cable	Yes

Accessories (Optional)

Spare Lamp Kit	Yes
Universal Ceiling Mount	Yes
3D Glasses	Yes

OSD

OSD Language	28L
--------------	-----