Engine/General Specifications

Configuration Desktop

Scanning Element Flatbed scanner with full color

contact image sensor (CIS)

Printing Process Electro-photographic printing

Toner Type Dry, single component

Control Panel 7" Smart Operation Panel

Color / Black & Color

White

Output Speed 30 ppm Copy/Print

First Page Out Time B&W: 7.2 seconds

Color: 8.6 seconds

Warm-Up Time 25 seconds

Recovery Time 9.9 seconds From Sleep Mode

Resolution Up to 1200 x 1200 dpi

System Memory 2 GB RAM

Maximum Copy 999 Copies Quantity

Duplexing Automatic (Standard)

Document Feeder
Type
Single Pass Document Feeder
(SPDF)

Document Feeder 5.5" x 5.5" to 8.5" x 23.6" (140 x 140 mm to 216 x 600 mm)

Document Feeder 14 \Box 34 lb. Bond (52 \Box 129 g/m2) Paper Weight Document Feeder 50 Sheets Capacity **Preset Reduction** 65%, 78%, 93%, 129%, 155% and Enlargement Ratios Zoom Range 25% to 400% in 1% increment Exposure Glass Size Up to 8.5" x 11.7" Maximum Original Platen: Up to 8.5" x 11.7"/A4 (216 x 297 mm) Size SPDF: Up to 8.5" x 23.6" (216 x 600 mm) Supported Paper Paper Tray: 3.25" x 5.83" □ 8.5" x 14.0" Sizes Bypass Tray: 2.52" x 5.0" \square 8.5" x 49.6 Supported Paper All Trays: 16-59 lb. bond (56-220g/m2)Weights Supported Paper Plain, Thick, Thin, Recycled, Color, Letterhead, Preprinted, Types Bond, Cardstock, Label, Glossy, Coated, Envelopes Standard Paper 1×250 -sheet Tray + 100-sheet Bypass Tray Capacity Maximum Paper 850 sheets Capacity Standard Output 150 sheets Capacity

Maximum Monthly Volume

Up to 7,500 prints

Maximum Duty

Cycle

75,000 prints

Power Source 120 V, 60Hz, 11A

Typical Electricity

0.498 kWh/week

Consumption (TEC)

TEC value is measured based on the ENERGY STAR

Ver.3.0 test method.

Power Consumption Operating: B&W: 469 W / Color:

512 W

Sleep Mode: 1.4 W

Energy Star Certified

EPEAT status Silver

Dimensions W x D

16.5" x 21.3" x 21.5" (420 x 540 x

xН

547 mm)

Weight 91.5 lbs. (41.5 kg)

Printer Specifications

Processor Speed 1.2 GHz

Interfaces Gigabit Ethernet (1000BASE-

T/100BASETx/10BASE-T)

USB 2.0 USB 2.0 Host IEEE802.11a/b/g/n

Network Protocol TCP/IP, Bonjour, DDNS

Supported Operating **Systems**

Windows: 7, 8.1, 10, Server 2008/R2, Server 2012/R2, Server

2016

Macintosh: OS X 10.9 or later Citrix, Linux, Unix, SAP R/3, IBM iSeries/AS/400 using OS/400 Host

Print Transform

Device Management **Utilities**

@Remote, Device Manager NX, Printer Driver Packager, Web

Image Monitor

Printer Languages PCL5c/6, PostScript3, PDF Direct

Print

Font Support PCL/PS3: 93 fonts

Print Resolution Up to 1200 x 1200 dpi

Mobile Printing

Support

RICOH Smart Device Connector,

AirPrint®, Google Cloud

Print□(Available Spring 2018),

Mopria®

Other Print Features Billing Code, Booklet (Magazine)

Print, Banner Page Print, Black Over Print, CMYK Simulation, Collate, Dithering, Duplexing, Do Not Print Blank Pages, Front Cover Sheet, Header/Footer, Layout/N-up Printing, Locked Print, Mirror Image Print, Mobile Device Printing, Reduce/Enlarge Print, Reverse Order Print, Rotate Print, User Codes, Watermarks

Security Features User Code Authentication, 802.1x

Wired Authentication,

Authentication Pwd Encryption, SSL/TLS, SMTP over SSL/TLS, Network Protocol On/Off, IP Filtering, SMTP over SSL, Windows Active Directory Support, Wireless LAN Security, Windows Authentication, LDAP Authentication, Kerberos, Basic

Authentication

Scanner Specifications

Scanning Resolution Color and B&W: up to 600 dpi

Scan Area Up to 8.5" x 14"

Protocols Network: TCP/IP

Email: SMTP

Scan-to Folder: SMB

File Formats JPEG, Single/Multi Page TIFF,

Single/Multi Page PDF

Scan Modes BW Text, BW Text/Photo, Gray

Scale, Full Color Text/Photo, Full

Color Glossy Photo

Scan-to-Email (POP, SMTP); Scan-to-Folder (SMB); Scan-to-Media (USB); TWAIN; Network

TWAIN

Fax Specifications

Fax Resolution Up to 200 dpi

Compression

Method

MH, MR, MMR

Scanning Speed 28 spm

Modem Speed 33.6 Kbps with automatic fallback

Transmission Speed Approximately 3 seconds/page -

ITU No.1 chart, Compression: MMR, Resolution: 200x100 dpi,

Standard speed: 33.6

SAF Memory SAF Memory: 2 GB

Page Memory: 4 GB

Max Auto Dials 400

Group Dials 20

Fax Features LAN-Fax, Fax Forwarding to E-

Mail/Folder, LDAP support,

PSTN, PBX