

JBL AC2212/00 Specs

PA Speaker

Configuration	Passive 2-Way
Enclosure Type	Bass-Reflex Loudspeaker
Total Power Capacity	Passive: 250 W RMS 1000 W Peak LF: 300 W RMS 1200 W Peak HF: 50 W RMS 200 W Peak
System Impedance	8 Ohms (Nominal)

Drivers

HF Driver	1 x Horn-Loaded Compression Driver with 1.5" / 3.81 cm Throat
HF Voice Coil	1.75" / 4.45 cm
MF Driver	<i>None</i>
LF Driver	1 x 12" / 30.48 cm Woofer
LF Voice Coil	2.5" / 6.35 cm

Performance

Frequency Range	50 Hz to 19 kHz -10 dB
Frequency Response	55 Hz to 17 kHz \pm 3 dB
Maximum SPL	120 dB (Continuous, Passive) 126 dB (Peak, Passive) 120 dB (LF, Continuous, Bi-Amp) 126 dB (LF, Peak, Bi-Amp) 126 dB (HF, Continuous, Bi-Amp) 132 dB (HF, Peak, Bi-Amp)
Coverage Angle	100° H x 100° V
Directivity	8.5 dB (Directivity Index) 7.1 dB (Directivity/Q Factor)
Speaker Sensitivity	Passive: 95 dB SPL LF: 95 dB SPL HF: 109 dB SPL
Protections	<i>None</i>

Connectivity

Audio I/O	1 x speakON NL4 Speaker Input (Lockable) 1 x Barrier Strip Speaker Input
-----------	---

Network I/O	<i>None</i>
-------------	-------------

USB	<i>None</i>
-----	-------------

Signal Processing

Crossover	1.3 kHz, 24 dB/Octave (Passive)
-----------	---------------------------------

EQ	<i>None</i>
----	-------------

Physical

Mounting	4 x M10 Fly Point (Top) 4 x M10 Fly Point (Bottom) 2 x M10 Fly Point (Each Side) 3 x M10 Fly Point (Rear) 4 x M8 Bracket Point (Rear)
----------	--

Handles	<i>None</i>
---------	-------------

IP Rating	IPX3
-----------	------

Construction Material	Perforated Metal Grille, Plywood
-----------------------	----------------------------------

Dimensions	14 x 21.6 x 13.9" / 35.5 x 54.8 x 35.2 cm
------------	--

Weight	42 lb / 19.1 kg
--------	-----------------

Packaging Info

Package Weight 48.2 lb

Box Dimensions (LxWxH) 23 x 15.25 x 15"
