

JBL AC299 Specs

Active or Passive	Passive
Frequency Response ± 3dB	80 Hz to 18 kHz
Frequency Range	-10 dB: 63 Hz to 20 kHz
Power Capacity	Long-Term System: 250 W/500 W/1000 W (Continuous/Program/Peak) System Power Rating (AES): 350 W (1400 W peak), 2 hours
Maximum Sound Pressure Level (SPL)	3.2' (1 m): 121 dB (127 dB peak)
Nominal Sensitivity	1 W @ 3.2' / 1 m: 97 dB
Impedance	8 Ohms
Crossover	1.5 kHz
Coverage Pattern	90 x 90°
Low Frequency Driver	1 x 12" (304.8 mm) woofer (P/N: 5050730) with 2.5" (63.5 mm) voice coil
High Frequency Driver	1 x 2408H-2 driver with 1" (25.4 mm) exit / 1.5" (38 mm) voice-coil

Enclosure Material	0.59" (15 mm) multi-ply hardwood plywood Grille: Powder coated, 0.05" (1.5 mm) perforated steel, with acoustically transparent black foam backing
Input Connections	Dual Neutrik NL4MP connectors plus covered barrier trip terminals
Mounting	14 x M10 threaded suspension points 4 x M10 for wall mount bracket
Dimensions	23.6 x 14.5 x 15.4" (600 x 368 x 391 mm)
Weight	38.3 lb (17.4 kg)