

JBL AC895 Specs

Active or Passive	Passive
Frequency Response ± 3dB	90 Hz to 18 kHz
Frequency Range	-10 dB: 70 Hz to 20 kHz
Power Capacity	Long-Term System Power Rating (IEC): 150 W/300 W/600 W (Continuous/Program/Peak) System Power Rating (AES): 250 W (1000 W peak), 2 hours
Maximum Sound Pressure Level (SPL)	3.2' (1 m): 116 dB (122 dB peak)
Nominal Sensitivity	1 W @ 3.2' / 1 m: 94 dB
Impedance	8 Ohms
Coverage Pattern	90 x 50° (H x V)
Crossover	2 kHz
Low Frequency Driver	1 x 8" (203 mm) woofer (P/N: 5050692) with 2" (50.8 mm) voice coil
High Frequency Driver	1 x 2414H-C driver with 1" (25.4 mm) exit/ 1" (25.4 mm) voice-coil
Enclosure Material	0.59" (15 mm) multi-ply hardwood

plywood
Grille: Powder coated, 0.05" (1.5 mm)
perforated steel, with acoustically
transparent black foam backing

Input Connections Dual Neutrik NL4MP connectors plus
covered barrier trip terminals

Mounting 14 x M10 threaded suspension points
4 x M10 for wall mount bracket

Dimensions 18.5 x 10.4 x 10" (470 x 265 x 254
mm)

Weight 22.4 lb (10.2 kg)

Packaging Info

Package Weight 28.2 lb

Box Dimensions (LxWxH) 22 x 13 x 12"
