

JBL AM5212 Specs

Active or Passive	Passive
Low Frequency Driver	1 x JBL 262H-1 12" / 305 mm Driver with 2" / 50.8 mm Dual Voice Coil Nominal Impedance: 8 Ohms Sensitivity: 97 dB SPL (1W @ 1m, within Operational Band)
High Frequency Driver	JBL 2408H-1, 1.5" / 38 mm Exit Compression Driver, 1.5" / 38 mm Voice Coil Nominal Impedance: 8 Ohms Sensitivity: 115 dB SPL (1W @ 1m)
Frequency Range	37 Hz to 20 kHz (-10 dB)
Frequency Response ± 3dB	43 Hz to 18 kHz
Coverage Pattern	60° x 40°
Coverage Modes	Bi-Amp / Passive Switchable
Directivity Factor	16.8 dB (Q)
Directivity Index	12.3 dB
Crossover Point	1.6 kHz (Passive)
Transducer Power Rating	400 W (1600 W Peak), 2 hr 300 W (1200 W Peak), 100 hr HF: 40 W (160 W Peak), 2 hr

Long-Term System Power Rating	300 W (1200 W Peak) 100 Hr (IEC)
-------------------------------	----------------------------------

Maximum SPL	Bi-Amp Mode: LF: 122 dB-SPL Cont Avg (128 dB Peak) HF: 131 dB-SPL cont avg (137 dB Peak)
-------------	--

System Sensitivity	Passive Mode: 115 dB SPL (1W @ 1m)
--------------------	------------------------------------

Horn Waveguide	PT-H64HF-1
----------------	------------

Enclosure Material	Trapezoidal with 15 Degree Side Angles, 5/8" / 16 mm Exterior Grade 11-Ply Birch Plywood
--------------------	--

Suspension Attachment	15 Points (4 Top, 4 Bottom, 2 each Side, 3 Rear), M10 Threaded Hardware
-----------------------	---

Finish	White DuraFlex Finish
--------	-----------------------

Grille	Powder Coated 14 Gauge Perforated Steel, with Acoustically Transparent Black Foam Backing
--------	---

Environmental Specifications	Mil-Std 810; IP-x3 per IEC529
------------------------------	-------------------------------

Dimensions	28.06 x 14.6 x 18.1" / 713 x 371 x 458 mm
------------	---

Weight	45 lb / 20.2 kg
--------	-----------------

Packaging Info

Package Weight 49 lb

Box Dimensions (LxWxH) 29.5 x 19.25 x 15.75"
