

JBL AM5215/95 Specs

Active or Passive	Passive
Low Frequency Driver	1 x JBL 265H-1 15" / 381 mm Driver with 2" / 50.8 mm Dual Voice Coil Nominal Impedance: 8 Ohms Sensitivity: 99 dB SPL (1W @ 1m, within Operational Band)
High Frequency Driver	JBL 2408H-1, 1.5" / 38 mm Exit Compression Driver, 1.5" / 38 mm Voice Coil Nominal Impedance: 8 Ohms Sensitivity: 113 dB SPL (1W @ 1m)
Frequency Range	35 Hz to 20 kHz (-10 dB)
Frequency Response ± 3dB	41 Hz to 18 kHz
Coverage Pattern	90° x 50°
Coverage Modes	Bi-Amp / Passive Switchable
Directivity Factor	11.6 dB (Q)
Directivity Index	10.6 dB
Crossover Point	1.8 kHz (Passive)
Transducer Power Rating	500 W (2000 W Peak), 2 hr 350 W (1400 W Peak), 100 hr HF: 40 W (160 W Peak), 2 hr

Long-Term System Power Rating	350 W (1400 W Peak) 100 Hr (IEC)
-------------------------------	----------------------------------

Maximum SPL	Bi-Amp Mode: LF: 125 dB-SPL Cont Avg (128 dB Peak) HF: 129 dB-SPL cont avg (135 dB Peak)
-------------	--

System Sensitivity	Passive Mode: 98 dB SPL (1W @ 1m)
--------------------	-----------------------------------

Horn Waveguide	PT-H95HF-1
----------------	------------

Enclosure Material	Trapezoidal with 15 Degree Side Angles, 5/8" / 16 mm Exterior Grade 11-Ply Birch Plywood
--------------------	--

Suspension Attachment	15 Points (4 Top, 4 Bottom, 2 each Side, 3 Rear), M10 Threaded Hardware
-----------------------	---

Finish	Black DuraFlex Finish
--------	-----------------------

Grille	Powder Coated 14 Gauge Perforated Steel, with Acoustically Transparent Black Foam Backing
--------	---

Environmental Specifications	Mil-Std 810; IP-x3 per IEC529
------------------------------	-------------------------------

Dimensions	30.8 x 16.6 x 19.85" / 83 x 422 x 504 mm
------------	--

Weight	55 lb / 25 kg
--------	---------------

Packaging Info

Package Weight 60.5 lb

Box Dimensions (LxWxH) 32 x 20 x 18.5"
