

# JBL AM7200 Specs

Active or Passive	Passive
Midrange Driver	1 JBL CMCD-82H Cone Midrange Compression Driver with integral 8" (200 mm) diameter Differential Drive dual voice-coil internal driver Nominal Impedance: 8 ohms Sensitivity: 108 dB SPL (1 W @ 1 m)
High Frequency Driver	JBL 2432H, 1.5" (38 mm ) exit compression driver, 3" (75 mm ) voice coil Nominal Impedance: 8 ohms Sensitivity: 113 dB SPL (1W @ 1m)
Frequency Range	260 Hz to 20 kHz (-10 dB)
Frequency Response &#177; 3dB	330 Hz to 18 kHz
Coverage Pattern	90° x 50°
Directivity Factor	11.0 dB (Q)
Directivity Index	10.5 dB
Crossover Supported	Bi-amp / Passive switchable
Crossover Frequency	2.2 kHz
Transducer Power Rating	MF: 350 W (1400 W peak), 2 hrs HF: 100 W (400 W peak), 2 hrs

---

Long-Term System Power Rating	MF/HF: 200 W (800 W peak), 100 hrs
-------------------------------	------------------------------------

---

Maximum SPL	Bi-amp Mode: MF: 133 dB-SPL cont avg (139 dB peak) HF: 133 dB-SPL cont avg (139 dB peak) Passive Mode: MF/HF: 133 dB-SPL cont avg (139 dB peak)
-------------	---

---

System Sensitivity	Passive mode: 108 dB dB SPL (1W @ 1m)
--------------------	---------------------------------------

---

Horn Waveguide	PT-K95MH
----------------	----------

---

Enclosure Material	Trapezoidal with 15 degree side angles, 5/8" (16 mm) exterior grade 11-ply Finnish birch plywood
--------------------	--

---

Suspension Attachment	13 points (3 top, 3 bottom, 2 each side, 3 rear), M10 threaded hardware
-----------------------	---

---

Finish	Black DuraFlex finish
--------	-----------------------

---

Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing
--------	---

---

Input Connection Type	NL4 Neutrik Speakon and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 0.2 sq" (5.2 sq mm) (10 AWG) wire or max width .375" (9 mm) spade lugs. Speakon in parallel with barrier strip for loop-through.
-----------------------	---

---

Environmental Specifications	Mil-Std 810; IP-x3 per IEC529
Dimensions	21.6 x 22.1 x 25.9" (548 x 561 x 657 mm)
Weight	60 lb (27.2 kg)

## Packaging Info

---

Package Weight	60 lb
Box Dimensions (LxWxH)	25.9 x 22.1 x 21.6"