

JBL AM7315/64 Specs

PA Speaker

Configuration	3-Way
Total Power Capacity	LF: 1000 W RMS 4000 W Peak MF: 350 W RMS 1400 W Peak HF: 100 W RMS 400 W Peak ⓘ
System Impedance	8 Ohms (Nominal)

Drivers

HF Driver	1 x Compression Driver with 1.5" / 38 mm Throat
HF Voice Coil	3" / 75 mm
MF Driver	1 x 8" / 200 mm Cone Compression Driver
MF Voice Coil	Dual
LF Driver	1 x 15" / 380 mm Woofer

Performance

Frequency Range	38 Hz to 20 kHz -10 dB
Frequency Response	45 Hz to 18 kHz \pm 3 dB
Maximum SPL	127 dB SPL (LF, Continuous, Tri-Amp) 133 dB (LF, Peak, Tri-Amp) 133 dB SPL (MF, Continuous, Tri-Amp) 139 dB (MF, Peak, Tri-Amp) 135 dB SPL (HF, Continuous, Tri-Amp) 141 dB (HF, Peak, Tri-Amp) 127 dB SPL (Continuous) 133 dB (LF, Continuous, Bi-Amp) 133 dB SPL (Continuous) 139 dB (HF, Peak, Bi-Amp)
Coverage Angle	60° H x 40° V (Rotatable Horn)
Directivity	13 dB
Speaker Sensitivity	108 dB SPL LF: 97 dB SPL MF: 108 dB SPL HF: 115 dB SPL

Connectivity

Audio I/O	1 x speakON NL8 Barrier Strip ⓘ
-----------	------------------------------------

Signal Processing

Crossover	Low-Pass: 300 Hz High-Pass: 2.3 kHz
-----------	--

Physical

Mounting	3 x M10 (Top) 3 x M10 (Bottom) 2 x M10 (Each Side) 3 x M10 (Rear)
----------	--

IP Rating	IP55
-----------	------

Construction Material	Perforated Metal Grille, Plywood
-----------------------	----------------------------------

Dimensions	38.1 x 22.1 x 25.9" / 967 x 561 x 657 mm
------------	--

Weight	101 lb / 45.8 kg
--------	------------------

Packaging Info

Package Weight	0.01 lb
----------------	---------
