

JBL ASB-6128V Specs

PA Speaker

Configuration	Passive Subwoofer
Enclosure Type	Horn / Folded Horn Subwoofer
Total Power Capacity	1600 W RMS 6400 W Peak ⓘ
System Impedance	4 Ohms (Parallel, Nominal) 2 x 8 Ohms (Discrete, Nominal)

Drivers

LF Driver	2 x 18" / 45.72 cm Woofer
LF Voice Coil	Dual 3" / 7.62 cm
Magnet	Neodymium

Performance

Frequency Range	22 Hz to 300 Hz -10 dB
Frequency Response	25 Hz to 300 Hz \pm 3 dB
Maximum SPL	132 dB (Continuous) 138 dB (Peak) ⓘ

Speaker Sensitivity

98 dB (Half-Space)ⁱ

Connectivity

Audio I/O	1 x speakON NL4 Speaker Input (Lockable) 1 x Barrier Strip Speaker Input
-----------	---

Network I/O	<i>None</i>
-------------	-------------

USB	<i>None</i>
-----	-------------

Signal Processing

EQ	<i>None</i>
----	-------------

Physical

Mounting	3 x M10 Fly Point (Top) 3 x M10 Fly Point (Bottom) 2 x M10 Fly Point (Each Side) 3 x M10 Fly Point (Rear)
----------	--

Handles	<i>None</i>
---------	-------------

IP Rating	IPX3
-----------	------

Construction Material	Perforated Metal Grille, Plywood
-----------------------	----------------------------------

Dimensions	22.1 x 38.1 x 47.8" / 56.1 x 96.7 x 121.5 cm
------------	--

Weight	198 lb / 89.8 kg
--------	------------------

Packaging Info

Package Weight

190 lb
