

# JBL AW566 Specs

Driver	Low Frequency Driver: JBL 2265H 15" / 380 mm Differential Drive driver with 3" / 75 mm dual voice coil High Frequency Driver: JBL 2432H 1.5" / 38 mm exit compression driver with 3" / 75 mm voice coil
Crossover Frequency	1.1 kHz
Frequency Range	35 Hz - 20 kHz
Frequency Response &#177; 3dB	54 Hz - 18 kHz
Coverage Pattern	60° x 60°
Directivity Factor	15.8
Directivity Index	12 dB
Impedance	8 ohms
Long-Term System Power Rating	600 W (2400 W peak), 100 hours
Sensitivity	100 dB SPL
Maximum Sound Pressure Level (SPL)	128 dB continuous average (134 dB peak)
Transformer Taps	70 V: 400W, 200 W, 100 W

100 V: 400W, 200W

---

Connectors Barrier strip terminals

---

Enclosure Material Fiberglass

---

Dimensions (HxWxD) 19.1 x 31.9 x 18.8" / 485.0 x 810.0 x 478.0 mm (measured when in horizontal orientation)

---

Weight 62.5 lb / 28.3 kg

---

## Packaging Info

---

Package Weight 76.2 lb

---

Box Dimensions (LxWxH) 35 x 23 x 20.5"

---