

JBL C24CT-BK Specs

Speaker

Active or Passive	Passive
Speaker Configuration	2-Way
Power Handling	40 W RMS 80 W Program
Constant Voltage / Transformer Taps	100 V: 30 / 15 / 7.5 W 70 V: 30 / 15 / 7.5 / 3.7 W

Drivers

HF Driver	0.75" / 19 mm Titanium-Coated Polyester
LF Driver	4" / 100 mm Polypropylene-Coated
LF Voice Coil	1" / 25.4 mm

Performance

Frequency Response	80 Hz to 20 kHz
--------------------	-----------------

Maximum SPL	102 dB
Sensitivity	86 dB SPL
Coverage Angle	130° H x 130° V
Directivity	2.4 (Directivity/Q Factor) 3.8 (Directivity Index)

Connectivity

I/O Connectors	2 x Screw Terminal Input 2 x Screw Terminal Thru/Output
Maximum Wire Gauge	12 AWG / 2.5 mm

Environmental

Certifications	UL, as per Manufacturer
----------------	-------------------------

Physical

Color	White
Cutout Depth	7.2" / 184 mm
Cutout Size	6.6" / 168 mm
Construction Material	Medium-Impact Polystyrene, Steel

Dimensions 7.7 x 7.9" / 195 x 200 mm

Weight 8 lb / 3.5 kg (Each Speaker)

Packaging Info

Package Weight 9.31 lb
