

# JBL Control 14C/T Specs

## Speaker

---

Active or Passive

Passive

---

Speaker Configuration

Full-Range

---

Power Handling

**At Low-Z:**  
60 W Program  
30 W RMS ⓘ

---

Constant Voltage /  
Transformer Taps

**100 V:**  
25 / 12.5 / 6.3 W  
**70 V:**  
25 / 12.5 / 6.3 / 3.2 W

---

Impedance

8 Ohms (Transformer Bypassed)

---

## Drivers

---

HF Driver

0.75" / 19 mm Silk Dome

---

LF Driver

4" / 100 mm Polypropylene-Coated  
Woofer

---

## Performance

---

Frequency Range

74 Hz to 20 kHz -10 dB

---

Frequency Response	100 Hz to 20 kHz $\pm$ 3 dB
--------------------	-----------------------------

---

Maximum SPL	102 dB 108 dB (Peak)
-------------	-------------------------

---

Sensitivity	87 dB <sup>ⓘ</sup>
-------------	--------------------

---

Coverage Angle	120° H x 120° V <sup>ⓘ</sup>
----------------	------------------------------

---

Directivity	8.1 dB (Directivity Index) 7.6 (Directivity/Q Factor) <sup>ⓘ</sup>
-------------	---

---

Crossover	12 dB/Octave
-----------	--------------

---

## Connectivity

---

I/O Connectors	Screw Terminal 4-Pin Input
----------------	----------------------------

---

Maximum Wire Gauge	12 AWG / 2.5 mm
--------------------	-----------------

---

## Environmental

---

Certifications	CE, UL, as per Manufacturer
----------------	-----------------------------

---

## Physical

---

Color	White
-------	-------

---

Cutout Size	6.7" / 170 mm <sup>ⓘ</sup>
-------------	----------------------------

---

Mount Surface Thickness Up to 1.4" / 35 mm ⓘ

---

Construction Material ABS, Glass

---

Dimensions 7.7 x 7.1" / 196 x 181 mm

---

Weight 4.8 lb / 2.2 kg (Each Speaker)

---

## Packaging Info

---

Package Weight 18 lb

---

Box Dimensions (LxWxH) 26.6 x 11.25 x 9.75"

---