

Image Sensor	CIS x 2
Light Source	LED
Optical Resolution	600 dpi
Hardware Resolution	600 x 600 dpi
Scan Modes	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit
ADF Capacity	20 Sheets (A4/ Letter, 70 g/m ² or 18 Lbs) 6 Sheets (Business Card)
Scanning Speed	20 ppm / 40 ipm (Grayscale, 200 dpi, A4) 20 ppm / 40 ipm (B&W, 200 dpi, A4) 20 ppm / 40 ipm (Color, 200 dpi, A4)
Scanning Area (W x L)	ADF: Maximum: 216 x 914.4 mm (8.5" x 36") Minimum: 12.7 x 12.7 mm (0.5" x 0.5") Cardslot: Maximum: 90.9 x 105 mm (3.58" x 4.13") Minimum: 12.7 x 12.7 mm (0.5" x 0.5")
Acceptable Paper Sizes (W x L)	ADF: Maximum: 216 x 914.4 mm (8.5" x 36") Minimum: 50.8 x 50.8 mm (2" x 2") Cardslot: Maximum: 90.9

x 105 mm
(3.58" x 4.13")
Minimum: 50.8
x 50.8 mm (2"
x 2")

Acceptable Paper Weight (Thickness)	Paper: 50 g/m ² to 120 g/m ² Plastic card: Non-Embossed up to 0.76 mm & Embossed up to 1.24 mm (ISO 7810)
Daily Duty Scan (Sheets)	1500
Roller Lifetime (Scans)	100000
Pad Lifetime (Scans)	20000
Action Button	PDF, BCR, Scan
Power Supply	AC adapter: 24 Vdc/ 0.75 A
Interface	USB 2.0
Net Weight	1.3 Kgs (2.87 Lbs)
Dimensions (W x D x H)	288.5 x 98 x 75 mm (11.36" x 3.8" x 2.96")
Protocol	TWAIN compliant
OS	Window XP / Vista / 7 / 8 / 10
Hardware Requirements	Pentium IV 2.4 GHz processor (Pentium IV 3.0 GHz processor recommended) DVD-ROM Driver One available USB 2.0 port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or

larger
recommended)
