

JBL Control 26-DT Specs

Active or Passive	Passive
Frequency Response	95 Hz - 18 kHz (-3 dB)
Power Capacity	60 Watts (transformer)
Maximum Sound Pressure Level (SPL)	106 dB @ 3.3 ft / 1 m
Nominal Sensitivity	89 dB SPL, 1 W @ 3.3 ft / 1 m
Transformer Taps	70 V Taps: 60, 30, 15, 7.5W 100 V Taps: 60, 30, 15W
Impedance	80 Ohms min. @ 247 Hz (60 Watts)
Crossover	3.5 kHz
Shielded	No
Low-Frequency Driver	6.5" Polypropylene-coated, 1" coil on aluminum former
High-Frequency Driver	.75" Titanium coated polyester
Mounting	4 screw holes at 7.6" / 194 mm diameter on center
Input Connections	Screw-locking Barrier Strip

Environmental	In accordance with IEC60849/EN60849 Safety Rating
---------------	--

Dimensions (HxD)	4.72 x 7.87" / 120 x 200 mm
------------------	-----------------------------

Weight	4.2 lb / 91.9 kg
--------	------------------

Specialties	Coaxial Speaker Design Multi-tap Transformer for 70 and 100V Systems Fits most Backcans 90° Coverage Pattern
-------------	--

Packaging Info

Package Weight	11 lb
----------------	-------

Box Dimensions (LxWxH)	21.6 x 10.2 x 6.5"
------------------------	--------------------
