

# JBL Control 312CS Specs

Active or Passive	Passive
LF Driver	12" / 30 cm Woofer with Kevlar-Reinforced Cone and 3" / 7.5 cm Voice Coil on Aluminum Former
Frequency Range	30 Hz to 4.5 kHz (-10 dB)
Frequency Response	34 Hz to 3.5 kHz ( $\pm 3$ dB)
Power Capacity	For 2 Hours: 400 W (1000 W Peak) For 100 Hours: 250 W (600 W Peak)
Sensitivity	93 dB (Measured Half-Space, 2.83 V at 1 m)
Maximum SPL	121 dB Continuous Average (124 dB Peak)
Nominal Impedance	8 Ohms
Input	Removable Locking Connector with Screw-Down Terminals (Input Terminals and Loop-Thru Output Terminals)
Maximum Wire Gauge	12 AWG
Shielded	No
Baffle	Material: Metal

Design: Ported, with EZRail for  
Backbox Installation  
Dimensions: 14.4 x 14.4" / 36.6 x 36.6  
cm

---

Dimensions (H x W x D) 14.4 x 14.4 x 6.3" / 36.6 x 36.6 x 16.0  
cm from Back of Baffle

---

Weight 17 lb / 7.7 kg

---

Safety Rating UL 1480, UL 2043, NFPA 90, and  
NFPA 70 when Installed with UL-  
Listed Backcan  
S7232/UL, UL 1876, IEC 60849 / EN  
60849

---

## Packaging Info

---

Package Weight 21 lb

---

Box Dimensions (LxWxH) 17.5 x 17.5 x 12.5"

---