

JBL Control 322CT Specs

Active or Passive	Passive
LF Driver	12" / 30 cm Woofer with Kevlar-Reinforced Cone and 3" / 7.5 cm Voice Coil
HF Driver	JBL 2407H Medium-Format Compression Driver with Neodymium Magnet and 1.5" / 3.7 cm Voice Coil
Frequency Range	32 Hz to 20 kHz (-10 dB)
Frequency Response	48 Hz to 19 kHz (± 3 dB)
Coverage Pattern	90° Conical, Broadband (Average 1 to 16 kHz)
Directivity Factor	9 (1 to 16 kHz)
Directivity Index	9.5 dB (1 to 16 kHz)
Power Capacity	For 2 Hours: 400 W (1600 W Peak) For 100 Hours: 250 W (1000 W Peak)
Sensitivity	Measured Half-Space: 95 dB (2.83 V at 1 m) Computed for Competitive Comparison: 100 dB (2.83 V at 1 m)
Maximum SPL	121 dB Continuous Average (124 dB Peak)

Impedance	Not applicable
Transformer Taps	Watts at 70 V: 12.5, 25, 50, 100 Watts at 100 V: 25, 50, 100
Insertion Loss	1 dB typical
Crossover	Frequency: 1.4 kHz Low-Pass Filter: 2nd Order (12 dB/Octave) High-Pass Filter: 3rd Order (18 dB/Octave)
Input	Removable Locking Connector with Screw-Down Terminals
Maximum Wire Size	12 AWG
Shielded	No
Baffle	Material: Metal Dimensions: 14.4 x 14.4" / 36.6 x 36.6 cm
Dimensions (H x W x D)	14.4 x 14.4 x 9.4" / 36.6 x 36.6 x 24.0 cm
Weight	22 lb / 10 kg
Safety Rating	UL 1480, UL 2043, NFPA 90, and NFPA 70 when Installed with a UL-Listed Backcan S7232/UL, UL 1876, IEC 60849 / EN 60849

Packaging Info

Package Weight 27.05 lb

Box Dimensions (LxWxH) 17.7 x 17.6 x 12.8"
