

JBL Control 328C Specs

Active or Passive	Passive
LF Driver	8" / 20 cm Woofer with Kevlar-Reinforced Cone and 2" / 5 cm Voice Coil
HF Driver	JBL 2412H-1 Compression Driver with 1" / 2.5 cm Voice Coil
Frequency Range	45 Hz to 18 kHz (-10 dB)
Frequency Response	60 Hz to 16 kHz (± 3 dB)
Coverage Pattern	120° Conical, Broadband
Directivity Factor	7 (1 to 16 kHz)
Directivity Index	8.5 dB (1 to 16 kHz)
Power Capacity	For 2 Hours: 250 W (1000 W Peak) For 100 Hours: 150 W (600 W Peak)
Sensitivity	Measured Half-Space: 93 dB (2.83 V at 1 m) Computed for Competitive Comparison: 98 dB (2.83 V at 1 m)
Maximum SPL	118 dB Continuous Average (124 dB Peak)
Impedance	8 Ohms

Transformer Taps	Not applicable
Crossover	Frequency: 1.9 kHz Low-Pass Filter: 2nd Order (12 dB/Octave) High-Pass Filter: 3rd Order (18 dB/Octave)
Input	Removable Locking Connector with Screw-Down Terminals
Maximum Wire Size	12 AWG
Shielded	No
Baffle	Material: Metal Diameter: 12" / 30.5 cm
Dimensions (Diam. x Depth)	12.0 x 6.3" / 30.5 x 16.0 cm from Back of Baffle
Weight	10 lb / 4.5 kg
Safety Rating	UL 1480, UL 2043, NFPA 90, and NFPA 70 when Installed with a UL-Listed Backcan S7232/UL, UL 1876, IEC 60849 / EN 60849

Packaging Info

Package Weight	14.6 lb
Box Dimensions (LxWxH)	15.6 x 15.4 x 12.9"