

# JBL Control 328CT Specs

Active or Passive	Passive
LF Driver	8" / 20 cm Woofer with Kevlar-Reinforced Cone and 2" / 5 cm Voice Coil
HF Driver	JBL 2412H-1 Compression Driver with 1" / 2.5 cm Voice Coil
Frequency Range	45 Hz to 18 kHz (-10 dB)
Frequency Response	60 Hz to 16 kHz ( $\pm 3$ dB)
Coverage Pattern	120° Conical, Broadband
Directivity Factor	7 (1 to 16 kHz)
Directivity Index	8.5 dB (1 to 16 kHz)
Power Capacity	For 2 Hours: 250 W (1000 W Peak) For 100 Hours: 150 W (600 W Peak)
Sensitivity	Measured Half-Space: 93 dB (2.83 V at 1 m) Computed for Competitive Comparison: 98 dB (2.83 V at 1 m)
Maximum SPL	118 dB Continuous Average (124 dB Peak)
Impedance	Not applicable

---

Transformer Taps	Watts at 70 V: 8.5, 17, 34, 68 Watts at 100 V: 17, 34, 68
------------------	--

---

Crossover	Frequency: 1.9 kHz Low-Pass Filter: 2nd Order (12 dB/Octave) High-Pass Filter: 3rd Order (18 dB/Octave)
-----------	---

---

Input	Removable Locking Connector with Screw-Down Terminals
-------	---

---

Maximum Wire Size	12 AWG
-------------------	--------

---

Shielded	No
----------	----

---

Baffle	Material: Metal Diameter: 12" / 30.5 cm
--------	--

---

Dimensions (Diam. x Depth)	12.0 x 8.6" / 30.5 x 21.8 cm from Back of Baffle
----------------------------	--

---

Weight	12 lb / 5.4 kg
--------	----------------

---

Safety Rating	UL 1480, UL 2043, NFPA 90, and NFPA 70 when Installed with a UL-Listed Backcan S7232/UL, UL 1876, IEC 60849 / EN 60849
---------------	---

---

## Packaging Info

---

Package Weight	16.85 lb
----------------	----------

---

Box Dimensions (LxWxH)

15.5 x 15 x 12.75"

---