

JBL CBT 1000E Specs

Active or Passive	Passive
Frequency Response	38 Hz to 650 kHz at -10 dB
Power Capacity	1500 W (6000 W peak), 2 hours 1000 W (4000 W peak), 100 hours These values conform to IEC standard, full bandwidth pink noise with 6 dB crest factor
Maximum Sound Pressure Level (SPL)	124 dB full space, 130 dB half-space (65 to 300 Hz) 2 to 6 kHz, calculated based on power rating and measured sensitivity, exclusive of power compression
Nominal Sensitivity	2.83 V at 3.3' (1 m), average 2 to 6 kHz: 92 dB full space 98 dB half-space (65 to 300 Hz)
Impedance	Nominal: 8 Ohms
Crossover	Not Specified by the Manufacturer
Low Frequency Driver	6 x 6.5" (165 mm) driver
Maximum Input Voltage	100 V RMS (2 hours) 200 V Peak (when powered)

separately, not in parallel with CBT 1000)

Enclosure Material	Fiberglass reinforced ABS cabinet, powder-coated 1050 aluminum grille
Inserts	Mounting Holes: 14 x M8 insert on back panel (20mm deep) for use with swivel pan/tilt bracket(s) (not included) Conform to the industry standard rectangular 5 x 2.75" (127 x 70 mm) pattern for OmniMount and other compatible third-party brackets (not included) 4 x M8 insert on top 4 x M8 insert on bottom of cabinet end-caps
Input Connections	Not Specified by the Manufacturer
Outdoor Use	IP-55 rated, per IEC529, when installed with optional MTC-PC2 panel cover. Exceeds Mil Spec 810 for humidity, temperature and UV, ASTM G85 for acid-air/salt-spray (200 hours)
Finish	Black (RAL9004)
Dimensions	9.9 x 40.2 x 11.6" (25 x 102 x 29 cm)
Weight	44 lb (20 kg)
