

# JBL CBT 200LA-1 Specs

Frequency Range	-10 dB: 80 Hz - 20 kHz
Frequency Response &#177; 3dB	130 Hz - 18 kHz (narrow coverage, music mode setting)
Vertical Coverage Angle	Narrow Mode: 15° Broad Mode: 30° Asymmetrical Progressive-Gradient Mode: 22°
Horizontal Coverage Angle	150°
Power Capacity	650 W, 2600 W peak (2 h) 400 W, 1600 W peak (100 h)
Maximum Sound Pressure Level (SPL)	Narrow Mode (speech): 123 dB, 129 dB peak Narrow Mode (music): 120 dB, 126 dB peak Broad Mode (speech): 121 dB, 127 dB peak Broad Mode (music): 118 dB, 124 dB peak Asymmetrical Progressive-Gradient Mode (speech): 122 dB, 128 dB peak Asymmetrical Progressive-Gradient Mode (music): 119 dB, 125 dB peak
Nominal Sensitivity	Narrow Mode(speech): 95 dB (2 - 5 kHz) Narrow Mode (music): 92 dB (150 Hz - 18 kHz) Broad Mode (speech): 93 dB (2 - 5 kHz)

Broad Mode (music): 90 dB (150 Hz - 18 kHz)  
Asymmetrical Progressive-Gradient Mode (speech): 94 dB (2 - 5 kHz)  
Asymmetrical Progressive-Gradient Mode (music): 91 dB (150 Hz - 18 kHz)

---

Drivers 32 x 2" (50 mm) drivers with dual neodymium magnets

---

Impedance 8 ohms

---

Enclosure Material Fiberglass reinforced ABS cabinet, painted aluminum grille

---

Connectors Two (one for top half and one for bottom half), screw-down terminal strip, zinc-plated copper base, nickel plated metal screws/washers. Accepts up to 9 mm outside 4 mm inside open lug (#6, #8 or #10 lug), or bare wire (up to 12 AWC/2.5 mm<sup>2</sup>)

---

Dimensions 78.7 x 3.9 x 6.0" / 200.0 x 9.9 x 15.3 cm

---

Weight 32.2 lb / 14.6 kg

---

## Packaging Info

---

Package Weight 46.08 lb

---

Box Dimensions (LxWxH) 49.61 x 19.88 x 8.35"

---