

JBL CBT 70JE-1 Specs

Frequency Range	45 - 700 Hz (-10 dB)
Power Capacity	500 W (2000 W peak), 2 hrs 350 W (1400 W peak), 100 hrs
Maximum Sound Pressure Level (SPL)	117 dB
Sensitivity	90 dB full space 96 dB half space
Nominal Impedance	8Ω
Voice Coil	1.5" (38 mm)
Low Frequency Driver	5" (130 mm) drivers x 8 pieces
High Frequency Driver	1" (25 mm) drivers x 16 pieces
Enclosure Material	Fiberglass-reinforced ABS cabinet, painted aluminum grille
Coverage	Vertical (selectable via switch) Narrow Mode: 25° (2 kHz - 16 kHz) (+/- 10°) Broad Mode: 45° (350 Hz - 16 kHz) (+/- 10°) Horizontal 150° (500 Hz - 18 kHz, +/- 20°)
Input Connections	2 x speaker wire terminals

Compliance	IP-54 rated per IEC529 UV, moisture and salt-spray resistant
------------	--

Dimensions (H x W x D)	54.8 x 6.7 x 9.3" (1388 x 170 x 237 mm)
------------------------	---

Weight	8.2 kg (18 lb)
--------	----------------

Packaging Info

Package Weight	27.5 lb
----------------	---------

Box Dimensions (LxWxH)	37.5 x 13.5 x 12"
------------------------	-------------------
