

JBL CSA1300Z Specs

Power Amplifier

Number of Channels	1
Power Rating	4 Ohms / 8 Ohms: 300 W (1 kHz, 0.5% THD)
Load Impedance / Voltage	4 Ohms (Minimum) 70 / 100 V

Performance

Frequency Response	20 Hz to 20 kHz \pm 1 dB (8 Ohms)
Input Sensitivity	Line: 775 mVrms (Balanced, at 8 Ohms) RCA: 300 mV (at 8 Ohms)
Input Impedance	Euroblock: 20 Kilohms (Balanced) RCA: 10 Kilohms
SNR	>97 dBA
THD	<0.5% (Full Range, at Rated Power)
Crosstalk	<-70 dBA (at 1 kHz)

Signal Processing

EQ 2-Band EQ ⓘ

Connectivity

I/O Euroblock Balanced/Unbalanced Input
2RCA Summed-Mono Input
Terminal Block Output

Power

AC Input Power 100 to 240 VAC, 50 / 60 Hz

Physical

Operating Temperature 32 to 95°F / 0 to 35°C ⓘ

Storage Temperature -4 to 185°F / -20 to 85°C

Dimensions 17.0 x 11.0 x 3.5" / 43.0 x 27.0 x 8.9 cm

Weight 13.1 lb / 5.9 kg

Packaging Info

Package Weight 15.7 lb

Box Dimensions (LxWxH)

21.6 x 14.5 x 6"
