

# JBL 240Z Specs

## Power Amplifier

---

Number of Channels	2
Power Rating	<b>4 Ohms / 8 Ohms:</b> 40 W (1 kHz, 0.5% THD)
Load Impedance / Voltage	4 Ohms (Minimum) 70 / 100 V

---

## Performance

---

Frequency Response	20 Hz to 20 kHz $\pm$ 0.5 dB (8 Ohms)
Input Sensitivity	1.4 Vrms
Input Impedance	<b>Euroblock:</b> 20 Kilohms (Balanced) <b>RCA:</b> 50 Kilohms
SNR	> 100 dB
THD	<0.5%
Crosstalk	> 70 dB

---

## Signal Processing

---

EQ 2-Band EQ ⓘ

---

## Connectivity

---

I/O **1 x** 2RCA Summed-Mono Input  
**2 x** Euroblock Input  
**2 x** Euroblock 70/100 V Output

---

Digital I/O **2 x** RJ45 (Control)

---

## Power

---

AC Input Power 100 to 240 VAC, 50 / 60 Hz

---

## Physical

---

Operating Temperature 32 to 95°F / 0 to 35°C

---

Storage Temperature -4 to 185°F / -20 to 85°C

---

Dimensions 8.6 x 11.9 x 1.7" / 218.5 x 303.4 x 43.3 mm

---

Weight 7.5 lb / 3.4 kg

---

## Packaging Info

---

Package Weight 10.9 lb

---

Box Dimensions (LxWxH) 16.2 x 12.1 x 5"

---