

JBL 280Z Specs

Power Amplifier

Number of Channels	2
Power Rating	4 Ohms / 8 Ohms: 80 W (1 kHz, 0.5% THD)
Load Impedance / Voltage	4 Ohms (Minimum) 70 / 100 V

Performance

Frequency Response	20 Hz to 20 kHz \pm 0.5 dB (8 Ohms)
Input Sensitivity	1.4 Vrms
Input Impedance	Euroblock: 20 Kilohms (Balanced) RCA: 50 Kilohms
SNR	> 100 dB
THD	<0.5%
Crosstalk	> 70 dB

Signal Processing

EQ **2-Band EQ** ⓘ

Connectivity

I/O **1 x 2RCA Summed-Mono Input**
2 x Euroblock Input
2 x Euroblock 70/100 V Output

Digital I/O **2 x RJ45 (Control)**

Power

AC Input Power **100 to 240 VAC, 50 / 60 Hz**

Physical

Operating Temperature **32 to 95°F / 0 to 35°C**

Storage Temperature **-4 to 185°F / -20 to 85°C**

Dimensions **8.6 x 11.9 x 1.7" / 218.5 x 303.4 x 43.3 mm**

Weight **8.8 lb / 4 kg**

Packaging Info

Package Weight 12 lb

Box Dimensions (LxWxH) 16.3 x 12.2 x 4.9"
