

JBL CSM 14 Specs

Inputs	4
Outputs	1
Line Output Level	5.0 V RMS into 10 kOhms
Frequency Response	20 to 20,000 Hz \pm 1 dB
Total Harmonic Distortion	0.05% typical
Signal to Noise Ratio	>90 dB
Input Impedance	Mic: 400 ohms Line: 20 kOhms RCA: 50 kOhms
Crosstalk	>70 dB
Tone Controls	Bass: \pm 10 dB at 100 Hz Treble: \pm 10 dB at 10,000 Hz
Input Sensitivity	Mic: 3 mV RMS Line: 300 mV RMS RCA: 300 mV RMS
Phantom Power	+27 VDC
Muting	Priority
Input/Output AC Line	100 to 240 V, 50/60 Hz

Voltage

Operating Temperature / Humidity	32 to 104°F (0 to 40°C) 95% R.H. (non-condensing)
----------------------------------	---

Storage Temperature	68 to 185°F (-20 to 85°C)
---------------------	---------------------------

Dimensions	1.7 x 8.6 x 11.9" (43.3 x 218.5 x 303.4 mm)
------------	---

Weight	4.3 lb (2.0 kg)
--------	-----------------

Packaging Info

Package Weight	7.36 lb
----------------	---------

Box Dimensions (LxWxH)	16.4 x 12.1 x 4.95"
------------------------	---------------------
