

# JBL CSM 28 Specs

Inputs	8
Outputs	2
Line Output Level	5.0 V RMS into 10 kOhms
Frequency Response	20 to 20,000 Hz $\pm$ 1 dB
Total Harmonic Distortion	0.05% typical
Signal to Noise Ratio	>90 dB
Input Impedance	Mic: 400 ohms Line: 20 kOhms RCA: 50 kOhms
Crosstalk	>70 dB
Tone Controls	Bass: $\pm$ 10 dB at 100 Hz Treble: $\pm$ 10 dB at 10,000 Hz
Input Sensitivity	Mic: 3 mV RMS Line: 300 mV RMS RCA: 300 mV RMS
Phantom Power	+27 VDC
Muting	Priority
Input/Output AC Line	100 to 240 V, 50/60 Hz

## Voltage

---

Operating Temperature / Humidity	32 to 104°F (0 to 40°C) 95% R.H. (non-condensing)
----------------------------------	---

---

Storage Temperature	68 to 185°F (-20 to 85°C)
---------------------	---------------------------

---

Dimensions	1.7 x 17.2 x 11.9" (43.3 x 437 x 303.4 mm)
------------	--

---

Weight	7.5 lb (3.4 kg)
--------	-----------------

---

## Packaging Info

---

Package Weight	11.3 lb
----------------	---------

---

Box Dimensions (LxWxH)	20.5 x 16.4 x 5.1"
------------------------	--------------------

---