

# JBL JBL Control 50 Pack Specs

## Speaker

---

Driver	2.5" / 60 mm Polypropylene Cone with Butyl Rubber Surround, Copper-Clad Aluminum Voice Coil, and Vented Nomex Former
Frequency Response	140 Hz - 20 kHz (-10 dB)
Power Capacity	50 W Continuous Program Power (2 Hours) 25 W Continuous Pink Noise (2 Hours) 30 W Continuous Program Power (100 Hours) 15 W Continuous Pink Noise (100 Hours)
Sensitivity	85 dB (4.0 V / 1 m = 1 W) 82 dB (2.83 V, 1 m)
SPL	94 dB, Average 100 dB Peak
Connectors	Removable Locking 2-Pin Connector with Screw-Down Terminals
Enclosure	High-Impact Polystyrene with Painted Zinc-Plated Metal Grille
Dimensions (HxWxD)	4.5 x 3.3 x 3.75" / 115 x 84 x 96 mm

---

Weight	1.5 lb / 0.7 kg
Subwoofer	
Driver	8" / 200 mm Polypropylene Cone with Butyl Rubber Surround, 1.5" 4-Layer Copper-Clad Voice Coil, and Vented Aluminum Former
Frequency Range	32 to 299 Hz (-10 dB)
Impedance	8 Ohms (Bypass/Thru Mode)
Maximum Power Handling	300 W Continuous (Program, 2 Hours) 150 W Continuous (Pink Noise, 2 Hours) 200 W Continuous (Program, 100 Hours) 100 W Continuous (Pink Noise, 100 Hours)
Maximum Sound Pressure Level (SPL)	115 dB Average, 121 dB Peak (Corner) 109 dB Average, 115 dB Peak (Center)
Controls and Indicators	1 x Volume Control
Connectors	6 x Removable Locking 2-Pin Connectors with Screw-Down Terminals
Shielded	No
Enclosure Material	Plywood and MDF Cabinet with Zinc-Plated Metal Grille
Dimensions (HxWxD)	14 x 15.4 x 8" / 356 x 391 x 203 mm

---

Weight

20 lb / 9 kg

---

## Packaging Info

---

Package Weight

33 lb

---

Box Dimensions (LxWxH)

21 x 18.3 x 11"

---