
Number of Printers included	2
Additional Parts	Cabinet
Printing Method	Epson Micro Piezo drop-on-demand inkjet technology, High-performance print head technology designed for robust printing environments, Variable Sized Droplet Technology
Printing Resolution	720x720dpi on Lustre Paper, 720x720dpi on Glossy Paper, 720x360dpi on Luster Paper, 720x360dpi on Glossy Paper, 1440x720dpi on Matte Paper, 1440x720dpi on Luster Paper, 1440x720dpi on Glossy Paper
Minimum Droplet Size	2.5 pl, With Variable-Sized Droplet Technology
Print Speed - High Speed	430 - 15 x 10 cm(6 x 4 ") prints/h
Print Speed - Standard	360 - 15 x 10 cm(6 x 4 ") prints/h
Print Speed - High Quality	180 - 15 x 10 cm(6 x 4 ") prints/h
Print Speed - Single Print using Quick Print Mode	in 17 sec - 15 x 10 cm(6 x 4 ") prints/h

Ink

Ink Technology	Ultrachrome® D6r-S
Ink Set	6 colours
Available Colours	Black, Cyan, Light Cyan, Light Magenta, Magenta, Yellow
Cartridge Size	200 ml

Media

Supported Media	Glossy, Lustre, Matte
------------------------	-----------------------

Media Handling	Roll Paper
No. Of Roll holders	1 pcs
Rear Roll specs	Max. Roll Length 66 m, Core Diameter 76 mm \pm 2 mm (3 inch), External Diameter 170 mm, Weight < 4 kg
Supported Media Width	102mm (4-inch), 127mm (5-inch), 152mm (6-inch), 203mm (8-inch), 210mm (A4), 89mm (3.5-inch)
Print Size	8.9 cm x 5 cm to 21 cm x 100 cm, 3.5 inches x 2 inches to 8.25 inches x 39 inches
Max. Print width	210 mm
Print Margins	Border defined by application, Borderless
Auto Cutter	Yes

General

Other Hardware	Control LED for roll paper and ink
Environmental Conditions - Temperature	Operating: 10 - 35 °C (except Matte), Matte: 15 - 25 °C, Storage: -20 - 40 °C
Environmental Conditions - Humidity	Operating 20 - 80 % (except Matte, no condensation), Storage 5 - 85 % (no condensation), Matte 40 - 60 % (no condensation)
Power Consumption	Operating (approx.) 120 W Ready Mode (approx.) 60 W Sleep Mode (approx.) 6 W
Voltage	100 V- 120 V, 200 V- 240 V, 50/ 60 Hz
Available Software	Printer Driver (standard bundling), Order Controller (optional)
Sound Pressure Level	< 50 dB (A) (ISO9296 Standard)
Compatible Operating Systems	Mac OS 10.5+, Windows 10 (32/64 bit), Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition
Interfaces	USB 2.0 Type A
Noise Level	Operation: 55 dB (A) Ready Mode: 43 dB (A)

Product dimensions	460 x 430 x 354 mm (Width x Depth x Height)
Product dimensions with tray	C12C934781
Product weight	23 kg without media and ink
What's in the box	CD Manual, Cabinet, Driver and utilities (CD), Inks, Maintenance Tank, Power cable, Setup guide, Spindle Unit(s)
