

JBL CONTROL 28-1L Specs

Speaker

Active or Passive	Passive
Speaker Configuration	2-Way
Power Handling	For 2 Hours: 240 W Program 120 W RMS
Impedance	8 Ohms (Nominal)

Drivers

HF Driver	1 x 1" / 25.4 mm PEI Dome Tweeter
LF Driver	1 x 8" / 203.2 mm Fiberglass Woofer

Performance

Frequency Range	45 Hz to 20 kHz -10 dB
Frequency Response	62 Hz to 16 kHz \pm 3 dB
Maximum SPL	118 dB SPL (Peak)

Sensitivity	91 dB
Coverage Angle	100° H x 100° V
Directivity	7.3 (Directivity/Q Factor)
Recommended High-Pass Filter	45 Hz, 24 dB/Octave
Maximum Input Voltage	55 V Peak

Connectivity

I/O Connectors	1 x Barrier Strip Speaker Input
Maximum Wire Gauge	12 AWG / 2.5 mm

Environmental

Certifications	RoHS, as per Manufacturer
Water / Weather Resistance	Weather Resistant
IP Rating	IP44

Physical

Color	Black
-------	-------

Mounting	1 x Ball Mount (Rear)
Dimensions	15.2 x 11.1 x 8.62" / 386 x 282 x 219 mm
Weight	13.5 lb / 6.1 kg

Packaging Info

Package Weight	29.2 lb
Box Dimensions (LxWxH)	22.5 x 17.5 x 13"