

JBL 126WT Specs

Active or Passive	Passive
LF Driver	6.5" / 16.5 cm Polymer-Coated Aluminum Cone with Pure Butyl Rubber Surround
HF Driver	1" / 2.5 cm Pure Titanium Dome with Cloth Suspension on Low-Diffraction Swivel Mount with -10° Aimability
Frequency Range	38 Hz to 20 kHz (-10 dB)
Power Capacity	Peak: 200 W Continuous Program: 100 W Continuous Pink Noise: 50 W
Sensitivity	88 dB SPL (1 W, 1 m)
Impedance	Not applicable
Transformer Taps	Watts at 70 V: 3.7, 7.5, 15, 30 Watts at 100 V: 7.5, 15, 30
Crossover	Low-Pass Filter to Woofer: 3rd Order (18 dB/Octave) High-Pass Filter to Tweeter: 3rd Order (18 dB/Octave)
Input	Screw-Down Euroblock Connector (14 AWG Maximum Wire Size)
Shielded	No

Air Gap	Optimum Air Cavity Behind Speaker: 0.7 to 1.4 ft ³ / 20 to 40 L
---------	---

Cutout Dimensions (H x W)	9.7 x 7.1" / 24.6 x 18.1 cm
---------------------------	-----------------------------

Maximum Wall Thickness	1.3" / 3.2 cm
------------------------	---------------

Dimensions (H x W x D)	11.0 x 8.5 x 4.1" / 28.0 x 21.5 x 10.5 cm 3.9" / 9.9 cm Front of Wall to Back of Speaker
------------------------	---

Weight	5.9 lb / 2.7 kg
--------	-----------------

Packaging Info

Package Weight	13.6 lb
----------------	---------

Box Dimensions (LxWxH)	12.5 x 10.5 x 9.5"
------------------------	--------------------
