

JBL Control 128W Specs

Active or Passive	Passive
LF Driver	8" / 20 cm Polymer-Coated Aluminum Cone with Pure Butyl Rubber Surround
HF Driver	1" / 2.5 cm Pure Titanium Dome with Cloth Suspension on Low-Diffraction Swivel Mount with -10° Aimability
Frequency Range	30 Hz to 20 kHz (-10 dB)
Power Capacity	Peak: 240 W Continuous Program: 120 W Continuous Pink Noise: 60 W
Sensitivity	90 dB SPL (1 W, 1 m)
Impedance	8 Ohms
Transformer Taps	Not applicable
Crossover	Low-Pass Filter to Woofer: 2nd Order (12 dB/Octave) High-Pass Filter to Tweeter: 2nd Order (12 dB/Octave)
Input	Screw-Down Euroblock Connector (14 AWG Maximum Wire Size)
Shielded	No

Air Gap	Optimum Air Cavity Behind Speaker: 1.4 to 2.8 ft ³ / 40 to 80 L
Cutout Dimensions (H x W)	11.9 x 8.9" / 30.0 x 22.5 cm
Maximum Wall Thickness	1.3" / 3.2 cm
Dimensions (H x W x D)	13.1 x 10.1 x 4.3" / 33.4 x 25.7 x 11.0 cm 4" / 10.2 cm Front of Wall to Back of Speaker
Weight	5.5 lb / 2.6 kg

Packaging Info

Package Weight	13.6 lb
Box Dimensions (LxWxH)	16 x 13 x 10"