

JBL CONTROL 25-1L Specs

Speaker

Active or Passive	Passive
-------------------	---------

Speaker Configuration	2-Way
-----------------------	-------

Power Handling	For 2 Hours: 200 W Peak 100 W RMS
----------------	--

Impedance	8 Ohms (Nominal)
-----------	------------------

Drivers

HF Driver	0.75" / 19.05 mm PEI Tweeter
-----------	------------------------------

LF Driver	5.25" / 133.35 mm Fiberglass Woofer
-----------	-------------------------------------

Performance

Frequency Range	60 Hz to 20 kHz -10 dB
-----------------	------------------------

Frequency Response	85 Hz to 17 kHz \pm 3 dB
--------------------	----------------------------

Maximum SPL	116 dB SPL
-------------	------------

Sensitivity	90 dB ⓘ
Coverage Angle	100° H x 100° V
Directivity	6.04 (Directivity/Q Factor) 7.6 dB (Directivity Index) ⓘ
Recommended High-Pass Filter	60 Hz, 24 dB/Octave
Maximum Input Voltage	25.3 V RMS 50.6 V Peak

Connectivity

I/O Connectors	Screw Terminal
Maximum Wire Gauge	12 AWG / 2.5 mm

Environmental

Certifications	RoHS, UL, as per Manufacturer
IP Rating	IP44

Physical

Color	Black
Construction Material	High-Impact Polystyrene, Metal Grille

Dimensions	9.57 x 7.4 x 5.71" / 243 x 188 x 145 mm
------------	---

Weight	6.7 lb / 3 kg
--------	---------------

Packaging Info

Package Weight	16 lb
----------------	-------

Box Dimensions (LxWxH)	16.5 x 16 x 11.3"
------------------------	-------------------
