

JBL Control 30 Specs

Speaker

Active or Passive	Passive
-------------------	---------

Speaker Configuration	3-Way
-----------------------	-------

Power Handling	For 100 Hours: 500 W Program 250 W RMS
----------------	---

Constant Voltage / Transformer Taps	70 V / 100 V
--	--------------

Impedance	4 Ohms
-----------	--------

Transformer Wattage	150 W
---------------------	-------

Shielded	No
----------	----

Drivers

HF Driver	1" / 25 mm Titanium-Coated Compression Driver
-----------	--

MF Driver	5" / 125 mm Aluminum Cone
-----------	---------------------------

MF Voice Coil	1" / 25 mm
---------------	------------

LF Driver	10" / 250 mm Fiberglass Woofer
-----------	--------------------------------

LF Voice Coil	2" / 5 cm
---------------	-----------

Performance

Frequency Response	38 Hz to 17 kHz -10 dB 40 Hz to 16 kHz \pm 3 dB
--------------------	--

Maximum SPL	123 dB (Peak) 117 dB (Continuous)
-------------	--------------------------------------

Sensitivity	93 dB
-------------	-------

Crossover	Low-Pass: 18 dB/Octave High-Pass: 18 dB/Octave
-----------	---

Protections	Overcurrent
-------------	-------------

Connectivity

I/O Connectors	1 x Screw Terminal
----------------	---------------------------

Environmental

Water / Weather Resistance	Weather Resistant
----------------------------	-------------------

IP Rating	IPX5
-----------	------

Physical

Color	Black
-------	-------

Construction Material	High-Impact Polystyrene
-----------------------	-------------------------

Dimensions	23.3 x 14.6 x 13.5" / 593 x 372 x 345 mm
------------	--

Weight	42 lb / 18.9 kg
--------	-----------------

Packaging Info

Package Weight	51.8 lb
----------------	---------

Box Dimensions (LxWxH)	28 x 18 x 18"
------------------------	---------------
