

JBL EON618S Specs

PA Speaker

Configuration	Active Subwoofer
---------------	------------------

Total Power Capacity	1000 W Peak 500 W RMS
----------------------	--------------------------

Drivers

LF Driver	1 x 18" / 45.72 cm Woofer
-----------	---------------------------

LF Voice Coil	2" / 5.1 cm
---------------	-------------

Performance

Frequency Range	31 Hz to 150 Hz -10 dB
-----------------	------------------------

Frequency Response	42.5 Hz to 150 Hz \pm 3 dB
--------------------	------------------------------

Maximum SPL	134 dB
-------------	--------

Gain Range	Line Input: 0 to 36 dBu
------------	-----------------------------------

I/O Impedance	Input: 22 Kilohms (Balanced)
---------------	--

Connectivity

Audio I/O	2 x Combo XLR-1/4" TRS Balanced Input 2 x XLR Male Thru/Output
-----------	---

Signal Processing

Crossover	80 to 120 Hz ⓘ
-----------	----------------

Power

AC Input Power	100 to 120 VAC, 50 / 60 Hz 230 to 240 VAC, 50 / 60 Hz
----------------	--

Current Consumption	1.14 A (Max, 1/8 Power) 1.71 A (Max, 1/4 Power) 2.03 A (Max, 1/3 Power)
---------------------	---

Physical

Mounting	1 x M20 (Top)
----------	----------------------

Handles	2
---------	---

Cooling	Convection
---------	------------

Construction Material	Perforated Metal Grille, Wood
-----------------------	-------------------------------

Dimensions	22.9 x 26.3 x 25.4" / 582 x 668 x 645 mm
------------	--

Weight	72 lb / 35.5 kg
--------	-----------------

Packaging Info

Package Weight	90 lb
----------------	-------

Box Dimensions (LxWxH)	31 x 30 x 24"
------------------------	---------------
