

JBL PD6200/64 Specs

PA Speaker

Configuration	Passive 2-Way
Enclosure Type	Horn / Folded Horn Loudspeaker
Total Power Capacity	Passive: 1200 W Peak (at 8 Ohms) Bi-Amp: 1400 W Peak 300 W Peak
System Impedance	1 x 8 Ohms (Nominal)

Drivers

HF Driver	1 x 1.5" / 38.1 mm Rotatable Horn Compression Driver with 1.5" / 38.1 mm Throat
HF Voice Coil	3" / 76.2 mm
MF Driver	1 x 8" / 203.2 mm Paper Cone Compression Driver
Magnet	MF: Neodymium

Performance

Frequency Range 200 Hz to 18 kHz -10 dB

Frequency Response 240 Hz to 16 kHz ± 3 dB

Maximum SPL
141 dB SPL (Passive)
141 dB SPL (MF, Bi-Amp)
141 dB SPL (HF, Bi-Amp)

Coverage Angle 60° H x 40° V (Rotatable Horn)

Directivity
13.5 dB (Directivity Index)
22.4 dB (Directivity/Q Factor)

Speaker Sensitivity
Passive:
110 dB SPL
Bi-Amp:
110 dB SPL
Bi-Amp:
116 dB SPL

Connectivity

Audio I/O
1 x 4-Core Cable NL4 Speaker Input (Lockable)
1 x Barrier Strip Speaker Input/Thru

Physical

Mounting **20 x** M10 (Bottom, Each Side, Rear, Top)

Construction Material	Metal Grille, Plywood
Dimensions	39 x 26.5 x 27.8" / 990.6 x 673.1 x 706.1 mm
Weight	130 lb / 59 kg