

# JBL PD6322/66 Specs

## PA Speaker

---

Configuration	Passive 3-Way
Enclosure Type	Horn / Folded Horn Loudspeaker
Total Power Capacity	<b>Passive:</b> 4800 W Peak (at 4 Ohms) 1200 W Peak (at 4 Ohms) <b>Tri-Amp:</b> 6400 W Peak 1400 W Peak 300 W Peak
System Impedance	<b>HF:</b> 1 x 8 Ohms (Tri-Amp) <b>MF:</b> 1 x 8 Ohms (Tri-Amp) <b>LF:</b> 2 x 8 Ohms (Tri-Amp)

---

## Drivers

---

HF Driver	1 x 1.5" / 38.1 mm Rotatable Horn Aluminum Compression Driver with 1.5" / 38.1 mm Throat
HF Voice Coil	4" / 101.6 mm
MF Driver	1 x 8" / 203.2 mm Horn-Loaded Cone Compression Driver

---

---

LF Driver	2 x 12" / 304.8 mm Woofer
-----------	---------------------------

---

LF Voice Coil	3" / 76.2 mm
---------------	--------------

---

Magnet	Neodymium
--------	-----------

---

## Performance

---

Frequency Range	41 Hz to 18 kHz -10 dB
-----------------	------------------------

---

Frequency Response	49 Hz to 16 kHz $\pm$ 3 dB
--------------------	----------------------------

---

Maximum SPL	141 dB SPL (Passive) 134 dB SPL (LF) 141 dB SPL (MF, Tri-Amp) 141 dB SPL (HF, Tri-Amp)
-------------	---

---

Coverage Angle	60° H x 60° V
----------------	---------------

---

Directivity	22.4 dB (Directivity/Q Factor) 13.5 dB (Directivity Index)
-------------	---

---

Speaker Sensitivity	<b>Passive:</b> 110 dB SPL <b>Tri-Amp/LF:</b> 96 dB SPL <b>Tri-Amp/MF:</b> 110 dB SPL <b>Tri-Amp/HF:</b> 116 dB SPL
---------------------	--

---

## Connectivity

---

Audio I/O

**1 x** speakON NL8 Speaker Input  
(Lockable)  
**1 x** Barrier Strip Speaker Input/Thru

---

## Signal Processing

---

Crossover

1.7 kHz (Passive)

---

## Physical

---

Mounting

**20 x** M10 (Bottom, Each Side, Rear,  
Top)

---

Construction Material

Metal Grille, Plywood

---

Dimensions

39 x 26.5 x 27.8" / 990.6 x 673.1 x  
706.1 mm

---

Weight

170 lb / 77.1 kg

---