

# JBL PD6322/95 Specs

## PA Speaker

---

Configuration	Passive 3-Way
Enclosure Type	Horn / Folded Horn Loudspeaker
Total Power Capacity	<b>Passive:</b> 4800 W Peak (at 4 Ohms) 1200 W Peak (at 4 Ohms) <b>Tri-Amp:</b> 6400 W Peak 1400 W Peak 300 W Peak
System Impedance	<b>HF:</b> 1 x 8 Ohms (Tri-Amp) <b>MF:</b> 1 x 8 Ohms (Tri-Amp) <b>LF:</b> 2 x 8 Ohms (Tri-Amp)

---

## Drivers

---

HF Driver	1 x 1.5" / 38.1 mm Rotatable Horn Aluminum Compression Driver with 1.5" / 38.1 mm Throat
HF Voice Coil	4" / 101.6 mm
MF Driver	1 x 8" / 203.2 mm Horn-Loaded Cone Compression Driver

---

---

MF Voice Coil	Dual 3" / 76.2 mm
LF Driver	<b>2 x</b> 12" / 304.8 mm Woofer
LF Voice Coil	3" / 76.2 mm
Magnet	Neodymium

---

## Performance

---

Frequency Range	41 Hz to 18 kHz -10 dB
Frequency Response	49 Hz to 16 kHz $\pm$ 3 dB
Maximum SPL	140 dB SPL (Passive) 134 dB SPL (LF) 140 dB SPL (MF, Tri-Amp) 139 dB SPL (HF, Tri-Amp)
Coverage Angle	90° H x 50° V (Rotatable Horn)
Directivity	10.5 dB (Directivity/Q Factor) 10.2 dB (Directivity Index)
Speaker Sensitivity	<b>Passive:</b> 109 dB SPL <b>Tri-Amp/LF:</b> 96 dB SPL <b>Tri-Amp/MF:</b> 109 dB SPL <b>Tri-Amp/HF:</b> 114 dB SPL

---

## Connectivity

---

Audio I/O	<b>1 x</b> speakON NL8 Speaker Input (Lockable) <b>1 x</b> Barrier Strip Speaker Input/Thru
-----------	--

---

## Signal Processing

---

Crossover	1.5 kHz (Passive)
-----------	-------------------

---

## Physical

---

Mounting	<b>20 x</b> M10 (Bottom, Each Side, Rear, Top)
----------	--

---

Construction Material	Metal Grille, Plywood
-----------------------	-----------------------

---

Dimensions	39 x 26.5 x 27.8" / 990.6 x 673.1 x 706.1 mm
------------	--

---

Weight	170 lb / 77.1 kg
--------	------------------

---