

Specifications

Frequency Range (± 10 dB)	200 Hz to 19.5 kHz
Frequency Response (± 3 dB)	230 Hz - 18.5 kHz
Coverage Pattern	40° x 30°
Directivity Index	16 dB
System Sensitivity (1W @ 1m):	Passive Mid-High: 110 dB SPL
Maximum Peak SPL (Bi-amplified mode)	MHF - 142 dB Peak
Transducer Power Rating (AES)	MHF - 400 W (1600 W Peak)
Crossover Frequencies	1.2 kHz
DSP	Custom DSP for Crown ITHD and IT4x3500HD amplifiers
Midrange Frequency Driver	2 x JBL CMCD-82H midrange driver with 200 mm (8 in) diameter Differential Drive® dual 75 mm (3 in) voice coil
High Frequency Driver	2 x JBL 2432H, 38 mm (1.5 in) exit compression driver, 75 mm (3 in) voice coil
Nominal Impedance	MF: 4 ohms HF: 16 ohms
Enclosure	Trapezoidal with Rectangular sides, combination of 18 mm and 16 mm (5/8 in) exterior grade birch plywood
Enclosure WRC/WRX Version	For direct exposure or extreme environments, berglassed with stainless steel hardware
Grille	Black powder coated zinc treated 14 gauge perforated steel with black foam backing

Grille WRC/WRX Version	Three layer grille assy consisting of 16-gauge powder coated S.S., backed with O.C. foam and S.S. mesh
Input Connector	NL4 for bi-amp operation
Input Connectors WRC/WRX Version	4 conductor 16 awg direct burial cable assy 20 length (or length TBD)
WRC/WRX Environmental Specifications	IP55
Suspension Attachment	52 total points (12 top and bottom, 11 each side, 6 back), M10 threaded hardwar
Dimensions (H x W x D)	991 mm x 991 mm x 1145.8 mm (39.0 x 39.0 x 45.1 in)
Net Weight	245 lbs (111.4 kg)