

JBL PRX412M Specs

| | |
|-----------------------|---|
| Active or Passive | Passive |
| Frequency Range | 50 Hz - 20 kHz (-10 db) |
| Frequency Response | 62 Hz - 19 kHz \pm 3 dB |
| Coverage Pattern | 90 x 50° |
| Crossover Type | Passive |
| Crossover Frequency | 2.0 kHz |
| Power Handling | 300 W continuous 600 W program 1200 W peak |
| Maximum SPL | 120 dB SPL continuous, 126 dB SPL peak |
| Sensitivity | 95 dB SPL (1 W @ 1 m) |
| Low Frequency Driver | 12" (305 mm) JBL MB112-8 woofer |
| High Frequency Driver | 1" (25 mm) JBL 2414H-C polymer diaphragm compression driver |
| Nominal Impedance | 8 ohms |

| | |
|-----------|--|
| Enclosure | Asymmetrical stage monitor 0.71" (18 mm) birch/poplar plywood |
|-----------|--|

| | |
|------------------|------------------------------|
| Mounting Options | Twelve M10 Suspension Points |
|------------------|------------------------------|

| | |
|-------------------------|--------------------------------------|
| Handle or Carrying Type | Glass-filled handle with rubber grip |
|-------------------------|--------------------------------------|

| | |
|--------|-----------------------|
| Finish | Black DuraFlex finish |
|--------|-----------------------|

| | |
|--------|--|
| Grille | Powder coated, black, 16-gauge perforated steel with acoustically transparent black screen backing |
|--------|--|

| | |
|------------------|--|
| Input Connectors | Parallel Neutrik Speakon NL-2 and 1/4" combo jacks |
|------------------|--|

| | |
|------------------------|---|
| Dimensions (H x W x D) | 22.6 x 13.9 x 15.7" (57.4 x 35.3 x 39.9 cm) |
|------------------------|---|

| | |
|--------|---------------|
| Weight | 35 lb (16 kg) |
|--------|---------------|

Packaging Info

| | |
|----------------|---------|
| Package Weight | 41.8 lb |
|----------------|---------|

| | |
|------------------------|---------------|
| Box Dimensions (LxWxH) | 24 x 21 x 17" |
|------------------------|---------------|
