

JBL PRX415M Specs

Active or Passive	Passive
Frequency Range	55 Hz - 19 kHz (-10 db)
Frequency Response	66 Hz - 19 kHz \pm 3 dB
Coverage Pattern	90 x 50°
Crossover Type	Passive
Crossover Frequency	2.2 kHz
Power Handling	300 W continuous 600 W program 1,200 W peak
Maximum SPL	122 dB SPL continuous, 128 dB SPL peak
Sensitivity	98 dB SPL (1W @ 1 m)
Low Frequency Driver	15" (380 mm) JBL MB115-8A woofer
High Frequency Driver	1" (25 mm) JBL 2414H-C polymer diaphragm compression driver
Nominal Impedance	8 ohms

Enclosure	Asymmetrical stage monitor 0.71" (18 mm) birch/poplar plywood
Mounting Options	Dual angle, 0° or -10° 35 mm pole socket Twelve M10 Suspension Points
Handle or Carrying Type	Two glass-filled handle with rubber grip
Finish	Black DuraFlex finish
Grille	Powder coated, black, 16-gauge perforated steel with acoustically transparent black screen backing
Input Connectors	Parallel Neutrik Speakon NL-2 and 1/4" combo jacks
Dimensions (H x W x D)	25.6 x 16.9 x 18" (650 x 429 x 457 mm)
Weight	46 lb (21 kg)

Packaging Info

Package Weight	55.4 lb
Box Dimensions (LxWxH)	28 x 23 x 22"