

## Specifications

Frequency Range (-10dB)	42Hz – 20kHz
Frequency Response (+/-3dB)	56Hz – 20kHz
Maximum Peak SPL(0dBV)	90 dB-SPL at 1m (0 dBV input; Max Volume setting, one channel)
Input Connectors	2 x RCA (left & right)
Nominal Input Sensitivity	-10 dBV for 85 dB-SPL at 1m (Max Volume setting)
HF DRIVER SIZE	2 x 19 mm (0.75”) Soft Dome Tweeter (one per channel)
LF DRIVER SIZE	4 x 51 mm (2.0”) Low-Frequency Driver (two per channel)
Power Amp	20W per Channel, Class D
Enclosure Material	Injection-Molded ABS
ENCLOSURE FINISH	Black
Mounting/Installation	Two included brackets, desk/table or on-wall mounting. See Owner’s Manual for installation diagrams.
AC power	Input: 100V-240VAC, 50/60Hz, 1.5A Sleep Mode Power: 0.25W at 100VAC; 0.36W at 240VAC
Dimensions (H x W x D)	90 x 900 x 65mm (3.54 x 35.4 x 2.55 in). See Owner’s Manual for dimensional drawing.
Weight	1.8kg (4.0lbs)
Shipping Weight	2.5kg (5.5lbs)
Included Accessories	See Owner’s Manual