

JBL SRX835P Specs

PA Speaker

Configuration	Active 3-Way
---------------	--------------

Total Power Capacity	2000 W Peak 1500 W RMS
----------------------	---------------------------

Amplifier Class	Class-D
-----------------	---------

Performance

Frequency Response	41 Hz to 20 kHz -3 dB
--------------------	-----------------------

Maximum SPL	137 dB
-------------	--------

Coverage Angle	60° H x 40° V
----------------	---------------

Gain Range	Line Input: 21 dB
	Aux Input: 3 dB
	Mic Input: 45 dB
	Line Input: 20 dBu
	Aux Input: 8 dBu
	Mic Input: -4 dBu

I/O Impedance

Input:

40 Kilohms (Balanced)

20 Kilohms (Unbalanced)

Connectivity

Audio I/O

2 x Combo XLR-1/4" TRS Input

2 x XLR 3-Pin Male Output

1 x XLR 3-Pin Mix Output

Signal Processing

Crossover

Low-Pass:

330 Hz

High-Pass:

2.4 kHz

Power

AC Input Power

100 to 240 VAC, 50 / 60 Hz

Current Consumption

120 VAC:

2.2 A (1/8 Power)

5.6 A (1/3 Power)

Physical

Mounting

1 x 1.4" / 36 mm Pole Socket

12 x M10

Handles 2

Cooling Fan (Variable Speed)

Construction Material Perforated Metal Grille, Plywood

Dimensions 38.7 x 21.4 x 18.7" / 98.4 x 54.4 x 47.6 cm

Weight 85 lb / 38.6 kg

Packaging Info

Package Weight 101 lb

Box Dimensions (LxWxH) 41 x 26 x 23"
