

## Specifications

Low Frequency Driver	4.5 in (118 mm)
High Frequency Driver	0.75 in (19 mm), soft dome
Crossover	1725 Hz, 1st order
Input Sensitivity	87 dB / 1 m
Power Amp	60 W (30 W each speaker), Class D
Maximum Continuous SPL @ 1 meter	89 dB
Maximum Peak SPL	102 dB
Maximum SPL	104 dB (momentary peak)
MAXIMUM PEAK INPUT LEVEL (-10dBV / +4dBu)	+6 dBV / +20.3 dBu
Frequency Range	60 Hz - 20 kHz
SYSTEM DISTORTION CRITERIA	<10% THD at maximum output with full compressor / limiter engagement
ELECTRICAL DISTORTION CRITERIA	<0.2%THD @ 1 kHz, 2.83 VRMS output; <1% THD @ 1 kHz, full rated output
Signal to Noise Ratio	75 dBA (A-Weighted), 70 dBr (unweighted), relative to 2.83 VRMS output on HF
COVERAGE HORIZONTAL x VERTICAL	120° x 60°
Dimension (H x W x D)	9.72 in x 6.02 in x 4.88 in (247 mm x 153 mm x 124 mm)
Net Weight	Master Monitor = 4.54 lb (2.06 kg); Slave Monitor = 3.81 lb (1.73 kg)
ENCLOSURE TYPE	Ported
Enclosure Material	ABS with metal grille
ENCLOSURE FINISH	Matte black acrylic paint
Audio Output Connectors	1 x 3.5 mm (1/8") stereo headphone with auto speaker mute
Audio Input Connectors	2 x 1/4-inch (6.5 mm) balanced (+4 dBu); 2 x RCA (-10 dBV); 1 x 1/8-inch (3.5 mm) unbalanced (-10 dBV)
AC INPUT VOLTAGE	100 – 240 VAC (± 10%), 50/60 Hz
Current Draw	85 watts