Tech Specs

Product features and specifications are subject to change without prior notice.

Technology

Scanner type	Flatbed Scanner, Sheetfed Scanner
Scanning Resolution	600 DPI x 600 DPI (Horizontal x Vertical)
ADF Minimum Document Size	68 mm x 120 mm (Horizontal x Vertical)
ADF Maximum Document Size	297 mm x 2,540 mm (Horizontal x Vertical)
Paper Formats	A3, A4, A5, A6, B4, B5, B6, Letter, Legal, Executive
Colour Depth	Input: 48 Bits Colour / 16 Bits Monochrome , Output: 24 Bits Colour / 8 Bits Monochrome
Ultrasonic Sensor	Yes
Application	High Capacity, General Office
Scanner	

CLOSE ALL

Light Source	ReadyScan LED technology
LCD Display	Optional Network Interface Panel

Scan speed

Scanning SpeedMonochrome: 40 pages/min - Color: 40 pages/min measured with size: A4 , resolution:
200 / 300 dpi, Monochrome: 80 image/min - Color: 80 image/min measured with size:
A4 , resolution: 200 / 300 dpi

Paper / Media Handling

ADF Paper weight	Auto loading: 35 - 128 g/m ²
Reliability Daily Duty Cycle	5,000 pages
Automatic Document Feeder	200 pages
Duplex Scan	Yes

Scanning Features

Features	Skip blank page, Pre-defined scanning settings, Automatic area segmentation, Automatic de-skew, Automatic multi-document recognition, Automatic B/W colour original detection, Dual Image Output (Windows only), Auto-rotation, Text enhancement, Edge fill, Unsharp Mask (USM), Descreening, Book spine correction, Automatic Folder Creation, Barcode Recognition, Zonal OCR A & B support, Manual / Automatic Job Separation
Output formats	JPEG, TIFF, multi-TIFF, PDF, PDF / batch, searchable PDF, secure PDF, PDF/A
File compression features	Hardware JPEG compression, TIFF Compression (JPEG(7) , CCITT G4, LZW), PDF Compression
Advanced document integration	Scan to Email, Scan to FTP, Scan to Microsoft SharePoint®, Scan to Print, Scan to Web folders, Scan to Network folders

Connectivity

Interfaces	USB 2.0 Type B, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (optional)
Network Interface Panel / Unit	Optional
Ethernet settings	10BASE-T / 100BASE-TX / 1000BASE-T / Full-duplex / Half-duplex
Panel type	5-line LCD with Push Scan features
Push scan features	Yes (with Document Capture Suite)

General

Supply Voltage	AC 100 V - 240 V
Product dimensions	640 x 522 x 289 mm (Width x Depth x Height)
Product weight	26.9 kg
Drivers	TWAIN, WIA, ISIS (Web download)
Included Software	Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Event Manager (Mac Only), Epson Scan, EpsonNet Config
Compatible Operating Systems	Citrix XenApp 5.0, Citrix XenApp 6.0, Mac OS 10.4+, Presentation Server 4.5, Terminal Service, Windows 7, Windows 7 x64, Windows 8, Windows Server 2003 (32/64bit), Windows Server 2008 R2, Windows Vista, Windows Vista x64, Windows XP, Windows XP x64, Windows Server 2003 R2
Energy Use	79 Watt, 12.5 Watt (economy), 1.5 Watt (standby)
Noise Level	Operation: 67.9 dB (A)
Humidity	Operation 10% - 80%, Storage 10% - 85%

Temperature	Operation 5° C - 35° C, Storage -25° C - 60° C
What's in the box	Main unit, Power cable, Setup guide, Software (CD), USB cable, Warranty document
Options	Roller Assembly Kit