

## Thermal

**Image Sensor** VOx Uncooled Focal Plane Arrays

**Resolution** 160×120

**Pixel Interval** 17μm

**Response Waveband** 8μm to 14μm

**NETD** Less than 40 mK (@25°C,F#=1.1)

**Focal Length** 6.2mm

**Focus Mode** Manual

**Field Of View** 25° × 18.7°

**IFOV** 2.74 mrad

**Image Frequency** 25 hz

**Aperture** F 1.1

## Optical

**Picture Resolution** Configurable: 2 MP, 5 MP, 8 MP

**Video Resolution** 640 × 480

## Thermography

**Rules** Max. Temperature; Min. Temperature; Center Temperature;  
Custom Point/Line/Area Thermography

**Thermographic Range** From 30 °C to 45 °C

**Accuracy** ± 0.5 °C

## Image Display

**Monitor** 640 × 480 resolution 3.5-inch LCD touch display

|                     |   |
|---------------------|---|
| <b>Image Mode</b>   | Thermal view, B/W optical view, image fusion view are selectable        |
| <b>Palettes</b>     | Black hot, White hot, Red hot, Rainbow, Ironbow, Fusion, Rain           |
| <b>Image Fusion</b> | Fusion view of thermal view and overlaid details of the optical channel |
| <b>Digital Zoom</b> | Thermal: 1×, 2×, 4×   |

### System Function

|                               |  |
|-------------------------------|--|
| <b>Laser Light</b>            | Support (Point to the thermography target)   |
| <b>Capture</b>                | Thermal/Optical/Fusion image   |
| <b>Video</b>                  | Thermal/Optical/Fusion image   |
| <b>Text Comment</b>           | Yes  |
| <b>Voice Comment</b>          | Yes  |
| <b>Wi-Fi</b>                  | Yes  |
| <b>Storage</b>                | Built-in memory module (16 G)  |
| <b>Client</b>                 | iVMS-4800 (PC);Hik-Thermal (Mobile APP)  |
| <b>Battery Type</b>           | Dismountable and rechargeable Li-ion Battery   |
| <b>Battery Operating Time</b> | 5 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off. 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on. |

### General

|                           |            |
|---------------------------|------------|
| <b>Hardware Interface</b> | Type-C USB |
| <b>Power Supply</b>       | 5 VDC/2 A  |
| <b>Power Consumption</b>  | Max. 4.5 W |

|                            |  |
|----------------------------|--|
| <b>Working Temperature</b> | -10 °C to 50 °C (14 °F to 122 °F)                              |
| <b>Protection Level</b>    | IP54   |
| <b>Drop Test Height</b>    | 2 m (6.56 feet)  |
| <b>Weight</b>              | With Battery: 653 g (1.44 lb) Without Battery: 511 g (1.13 lb) |
| <b>Dimension</b>           | 244 mm × 100 mm × 104 mm (9.6 " × 3.9 " × 4.1 ")               |