
| | |
|-----------------------------|--|
| Printing Method | PrecisionCore™ Micro TFP printhead |
| Nozzle Configuration | 8,676 Nozzles Black, 8,676 Nozzles per Color |
| Minimum Droplet Size | 3.5 pl |
| Ink Technology | DURABrite™ Pro |
| Application | Office Departmental |
| All-in-One Functions | Print, Scan, Copy, Fax |

Print

| | |
|---|--|
| First Page Out from Ready | Monochrome 5 Seconds, Colour 5 Seconds |
| Printing Speed ISO/IEC 24734 | 100 pages/min Monochrome, 100 pages/min Colour |
| Duplex Printing Speed ISO/IEC 24734 | 100 A4 pages/min Monochrome, 100 A4 pages/min Colour |
| Printing Speed ISO/IEC 24734 (A3) | 54 pages/min Monochrome, 54 pages/min Colour |
| Duplex Printing Speed ISO/IEC 24734 (A3) | 36 A4 pages/min Monochrome, 36 A4 pages/min Colour |
| Printing Speed | 100 pages/min Monochrome (plain paper 75 g/m ²), 100 pages/min Colour (plain paper 75 g/m ²) |
| Printing Resolution | 600 x 2,400 DPI |
| Max Duty cycle | 400,000 pages per month |
| Recommended Duty Cycle | 8,000 - 100,000 pages per month |
| Colours | Black, Cyan, Yellow, Magenta |

Scan

| | |
|--------------------------------------|---|
| Scanning Speed (new) | 60 ipm (Monochrome, Single-sided, 200 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; 110 ipm (Monochrome, Double-sided, 200 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; 60 ipm (Colour, Single-sided, 200 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; 110 ipm (Colour, Double-sided, 200 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; 60 ipm (Colour, Single-sided, 300 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; 85 (Colour, Double-sided, 300 dpi, ADF) * Scanning in accordance with ISO/IEC 17991; |
| Scanning Resolution | 600 DPI x 1,200 DPI (Horizontal x Vertical) |
| Optical Resolution (ADF) | 600 DPI x 600 DPI (Horizontal x Vertical) |
| Advanced document integration | Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB Memory Device |
| Output formats | JPEG, TIFF, PDF |
| Scanner type | Contact image sensor (CIS) |

Fax

| | |
|-------------------------------|--|
| Type of fax | Walk-up black and white and colour fax capability |
| Fax Transmission Speed | upto 33.6kbps / Approx. 3 sec/page |
| Error correction mode | CCITU/ITU Group3 fax with Error Correction Mode |
| Fax speed dials (max) | 2,000 names and numbers |
| Page memory | upto 550 pages/ 6MB (ITU-T No. 1 chart) |
| Fax Functions | Auto Redial, Address Book, Delay Send, Broadcast Fax |

Copy

| | |
|---------------------------------|--|
| Copy Speed | Up to 100 ipm Black, Up to 100 ipm Colour *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) |
| Copy resolution (dpi) | 600 x 1200 |
| Reduction / Enlargement | 25 % - 400 % |
| Maximum number of copies | 9,999 |
| Maximum Copy Size | A3 |

Connectivity

| | |
|-------------------------------------|---|
| Network Printing Protocols | LPR, FTP, IPP, LPD, Port 9100, TCP/IPv4, TCP/IPv6, IPSec, WSD-Print |
| Network Management Protocols | SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, TCP/IPv4, TCP/IPv6, IPSec, IEEE 802.1X, DCHP, HTTPS, LDAP, SNMP 3.0 |
| Network Scanning Protocols | WSD-Scan, FTP |
| Interfaces | 10 Base-T, Wired Network, Gigabit ethernet interface, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct, USB 1.1 Type A, USB 2.0 Type A, USB 3.0 Type B, Near Field Communication (NFC) |
| Network Protocols | TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS |

Paper / Media Handling

| | |
|----------------------------------|---|
| Paper Formats | A3, A4, Postcard, A3+, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Executive, Letter, Legal, HLT, No. 10 (Envelope), User defined |
| Automatic Document Feeder | 150 pages |
| Compatible Paper Weight | 60 g/m ² - 350 g/m ² |

| | |
|------------------------------|--|
| Duplex | Yes (A4/A3, plain paper) |
| Standard Paper input | 2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray |
| Output Tray Capacity | 550 Sheets |
| Maximum paper input | 5,350 |
| Number of paper trays | 4 |

Paper Feed

| | |
|--------------------------------|--|
| Paper Input Name | RASF |
| Paper Formats | A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Letter, 20 x 25 cm, HLT, User defined |
| Custom sizes | Min 55x 330 mm to Max 127x 1,200 mm |
| Compatible paper weight | 60 g/m ² - 350 g/m ² |
| Paper Capacity 1 | 150 80gsm |

Paper Feed

| | |
|--------------------------------|--|
| Paper Input Name | C1 |
| Paper Formats | A3, A4, A5, B4, B5, Letter, HLT, Executive |
| Custom sizes | Min 140x 297 mm to Max 182x 432 mm |
| Compatible paper weight | 60 g/m ² - 160 g/m ² |
| Paper Capacity 1 | 550 80gsm |

Paper Feed

| | |
|--------------------------------|--|
| Paper Input Name | C2-C4 |
| Paper Formats | A3, A4, A5, B4, B5, Letter, HLT |
| Custom sizes | Min 140x 297 mm to Max 182x 432 mm |
| Compatible paper weight | 60 g/m ² - 160 g/m ² |
| Paper Capacity 1 | 550 80gsm |

Paper Feed

| | |
|--------------------------------|--|
| Paper Input Name | LCT |
| Paper Formats | A4, Letter |
| Compatible paper weight | 60 g/m ² - 160 g/m ² |
| Paper Capacity 1 | 3,000 80gsm |

Paper Feed

| | |
|--------------------------------|--|
| Paper Input Name | Duplex |
| Compatible paper weight | 60 g/m ² - 160 g/m ² |

General

| | |
|---------------------------|---|
| Energy Use | 180 Watt (standalone copying, ISO/IEC 24712 pattern), 1.4 Watt (sleep mode), 77 Watt (ready), 0.4 Watt (Power off), TEC 0.46 kWh/week |
| Supply Voltage | AC 100 V - 240 V |
| Product dimensions | 674 x 757 x 1,231 mm (Width x Depth x Height) |
| Product weight | 179 kg |

| | |
|-------------------------------------|--|
| Compatible Operating Systems | Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.6.8, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP SP2 or higher, Windows Server 2003 R2, Windows XP Professional x64 Edition |
| Sound Power | Operation: 7.5 B (A) |
| Sound Pressure | Operation: 59 dB (A) |
| Power Supply | 220V, 240V |
| What's in the box | Information sheet, Power cable, User guide |

Additional Features

| | |
|---------------------------|--|
| Features | Touchscreen |
| LCD screen | Type: Colour, Touchscreen, Diagonal: 22.7 cm |
| Media Handling | Duplex (A4/A3, plain paper) |
| Security Functions | Limit access function with Epson Web Config, Secure confidential printing with PIN code release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin Mode |

Other Features

| | |
|-------------------|---|
| Emulations | PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour |
|-------------------|---|
