Scanner type	Sheetfed Scanner
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)
Scanning Resolution	600 DPI x 600 DPI (Horizontal x Vertical)
Paper Formats	A4, A5, A7, A6, B6, B5, B4, A3 with stitching function, Letter, Postcard, Legal, Business cards, Plastic cards
Colour Depth	Input: 30 Bits Colour / 10 Bits Monochrome , Output: 24 Bits Colour / 1 Bits Monochrome
Ultrasonic Sensor	Yes
Application	Small & Compact, High Capacity

Scanner

Optical Sensor	CIS (Contact Image Sensor)
Output Resolution	1200 DPI

LCD Display	Epson Network Interface Panel
-------------	-------------------------------

Scan speed

Scanning Speed	Monochrome: 65 pages/min - Color: 65 pages/min measured with size: A4 , resolution:
	200 / 300 dpi, Monochrome: 130 image/min - Color: 130 image/min measured with size:
	A4 , resolution: 200 / 300 dpi

Paper / Media Handling

ADF Paper Setting 100 Sheets Capacity

ADF Paper weight	Auto loading: 27 - 413 g/m ²
Automatic Document Feeder Type	Single pass dual scanning
Reliability Daily Duty Cycle	7,000 pages
Automatic Document Feeder	100 pages
Duplex Scan	Yes

Scanning Features

Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG
File compression features	TIFF Compression (JPEG(7) , CCITT G4, LZW), PDF Compression, JPEG compression
Advanced document integration	Scan to Email, Scan to FTP, Scan to Microsoft SharePoint®, Scan to Print, Scan to Network folders, Scan to USB
Scanning Volume	7,000 pages per day

Connectivity

Interfaces	Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T)
Protocol support	TCP/IP, DHCP, DNS, SNMP, SLP
IPv6 support	Yes
Push scan features	Yes (with Document Capture Suite)
Panel Lock with password	Yes (with Document Capture Suite)

Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Energy Use	18 Watt (Operation), 8.5 Watt (ready), 1.4 Watt (sleep mode), 0.1 Watt (Power off)
Drivers	TWAIN, ISIS (Web download), Epson Scan2 (TWAIN), SANE (Linux), WIA (Windows)
Included Software	Document Capture Pro 2.0, Epson Device Admin, Epson Scan 2
Compatible Operating Systems	Mac OS 10.10.x, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP
Humidity	Operation 15% - 80%, Storage 15% - 85%
Temperature	Operation 5° C - 35° C, Storage 25° C - 60° C
What's in the box	AC Adaptor, Driver and utilities (CD), Main unit, Power cable, Setup guide, USB cable, Warranty card
Options	Roller Assembly Kit