Scanner type Sheetfed Scanner

Scanning Resolution 600 DPI x 600 DPI (Horizontal x Vertical)

ADF Minimum Document

Size

50.8 mm x 50.8 mm (Horizontal x Vertical)

ADF Maximum Document

Size

215.9 mm x 6,096 mm (Horizontal x Vertical)

Paper Formats A4, A5, A6, B5, B6, Letter, Postcard, Business cards, Plastic cards, Legal, Executive, A3 with

stitching function

Colour Depth Input: 30 Bits Colour / 10 Bits Monochrome , Output: 24 Bits Colour / 8 Bits Monochrome

Ultrasonic Sensor Yes

Application High Capacity, General Office

Scanner

Light Source ReadyScan LED technology

Scan speed

Scanning Speed Monochrome: 35 pages/min - Color: 35 pages/min measured with size: A4, resolution: 200 / 300

dpi, Monochrome: 70 image/min - Color: 70 image/min measured with size: A4, resolution: 200

/ 300 dpi

Paper / Media Handling

ADF Paper Setting Capacity 50 Sheets

ADF Paper weight Auto loading: 27 - 413 g/m²

Automatic Document Feeder

Type

Single pass dual scanning

Reliability Daily Duty Cycle

4,000 pages

Automatic Document Feeder

50 pages

Duplex Scan

Yes

Scanning Features

Features RGB colour dropout, Advanced Colour Dropout / Enhance, Skip blank page, A3 stiching, Punch

holes removal, Advanced editing, Automatic de-skew, Automatic multi-document recognition, RGB colour enhance, Dual Image Output (Windows only), Auto-rotation, Text enhancement, Edge fill, Unsharp Mask (USM), Descreening, Automatic Folder Creation, Barcode Recognition,

Zonal OCR A & B support, Full Zonal OCR

Output formats JPEG, TIFF, multi-TIFF, PDF, searchable PDF, secure PDF, PDF/A

File compression features Hardware JPEG compression, TIFF Compression (JPEG(7), CCITT G4, LZW), PDF

Compression

Advanced document

integration

Scan to Email, Scan to FTP, Scan to Microsoft SharePoint®, Scan to Print, Scan to Web folders,

Scan to Network folders

Connectivity

Interfaces USB 3.0, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (optional)

Network Interface Panel /

Unit

Optional

Ethernet settings 10BASE-T / 100BASE-T / 1000BASE-T / Full-duplex / Half-duplex

Panel type 5-line LCD with Push Scan features

Protocol support TCP/IP, DHCP, DNS, SNMP, SLP

IPv6 support Yes

Push scan features Yes (with Document Capture Suite)

Panel Lock with password Yes (with Document Capture Suite)

General

Product dimensions 296 x 169 x 176 mm (Width x Depth x Height)

Product weight 3.7 kg

Drivers TWAIN, WIA, ISIS (Web download)

Included Software Epson Document Capture (Mac only), Epson Document Capture Pro (Windows only), Epson

Document Capture Pro Server (on free download), Epson Scan 2, Newsoft Presto BizCard 5.6

Compatible Operating

Systems

Citrix XenApp 5.0, Citrix XenApp 6.0, Citrix XenApp 7.6 and above, Linux, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.6.8, Windows 10, Windows 7,

Windows 7 x64, Windows 8, Windows 8 (32/64 bit), Windows 8 RT, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Vista, Windows Vista x64, Windows Server 2003

R2, Windows XP Professional x64 Edition

Energy Use 17 Watt, 9.2 Watt (economy), 1.2 Watt (standby)

Humidity Operation 15% - 80%, Storage 15% - 85%

Temperature Operation 5° C - 35° C, Storage -25° C - 60° C

What's in the box Driver and utilities (CD), Main unit, Power cable, Setup guide, USB cable, Warranty document

Options Roller Assembly Kit